

FENCING & PALLET COIL NAILER



CN550S



drives 25~50mm conical wire welded nails
and flat plastic sheet collated nails

FEATURES

- **Lightweight-only 2.0 kg**
- **Rapid fire trigger valve**
Comes with standard rapid-fire trigger valve for high-speed fastening.
- **Runs both conical wire welded nails and plastic sheet collated nails without any adjustment**
- **Maintenance free end cap filter (US Patent 5637125)**



parts last longer and the inside of the tool is kept clean. The filter has a self-cleaning feature; foreign substances are ejected automatically from the tool when the air hose is disconnected.



APPLICATIONS

- Fencing
- Pallets and pallet repair
- Sub-flooring
- Wall sheathing and roof sheathing

TOOL SPECIFICATIONS

MODEL	CN550S
WEIGHT	2.0kg (4.4lbs)
DIMENSIONS	270(H)×125(W)×270(L)mm 10-5/8"×4-7/8"×10-3/4"
LOAD CAPACITY	400 nails (Wire welded nails) 200 nails (Plastic sheet collated nails)
OPERATING PRESSURE	4~7kg/cm ² (Regulator) 60~100p.s.i.
AIR CONSUMPTION	1.6l/cycle at 6 bar (90p.s.i.) operating pressure
NOISE	A-weighted single-event sound power level LWA, 1s, d 91.96dB A-weighted single-event emission sound pressure level at work station LpA, 1s, d 84.92dB These values are determined and documented in accordance to CEN/TC 255 WG 1 N 45.3 E. (EN-standard in preparation)
VIBRATION	Vibration characteristic value = 3.45m/s ² These values are determined and documented in accordance to ISO 8662-11



360° Flexible Tailpiece



- **Dial adjustable depth control**
Dial depth control requires no special tools.




- **Easy twist adjustable exhaust deflector**
Exhaust air can easily be diverted 360° away from user without any tool.

- **Comfortable rubber grip**
- **Built-in sound reducer**
Reduce decibel level to make the tool more user friendly.
- **No-mar contact tip included**

FASTENERS APPLICABLE

▼ Collation Type

15 degree conical wire welded nails



15 degree flat plastics sheet collated nails.



▼ Shank Type

Head diameter
4.2mm~5.3mm

Smooth
Screw and
Ring Shank

Shank diameter
1.59mm~2.5mm



The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.



MAX CO., LTD.

6-6 NIHONBASHI HAKOZAKI-CHO, CHUO-KU, TOKYO, JAPAN
PHONE: 03-3669-8131 FAX: 03-3669-7104
<http://www.max-ltd.co.jp/int/>

Distributor:



Printed on
Recycled Paper

PRINTED IN JAPAN
OS101AN T0107