

Product Data Sheet

No. **1261** - 03/21

INVERT-A-CAP MARKING PAINT

CARB MIR ≤ 0.85 (Ground Traffic/Marking Coating)

PRODUCT NUMBERS:

261 - RED	267 - WHITE	274 - FL. GREEN
262 - YELLOW	270 - FL. RED	275 - FL. RED-ORANGE
263 - BLUE	272 - FL. ORANGE	279 - FL. PINK
265 - ORANGE		

I. GENERAL DESCRIPTION

Features: This quality marking paint is packaged in a can that may only be operated in an upside down position. It is formulated to meet a variety of marking applications while still providing good initial color visibility, good color retention, and adhesion. Packaged in a 16 oz. can for writing convenience and comfort.

Benefits: Provides great color durability for up to 3 months, depending on traffic and exposure. It meets standards set by OSHA and APWA/ONE Call Systems. It is not affected by moisture or water and it will not wash away once dry. Can be used with the cap on in Aervoe applicators #1244/1245. The spray-through cap eliminates accidental discharge. Each can is non-clogging and empties completely.

Uses: Designed to adhere to most surfaces, including pavement, gravel, and soil. It can be used for marking at construction sites, locator and utility identification, landscaping, or other general marking requirements. It is not recommended for use on short cut grass such as golf course greens.

Application: Shake can well before use and for 1 to 2 minutes after agitator ball is heard. Remove tab from tamper-resistant cap. With proper alignment of the activator bar, this product can be used with the cap on in Aervoe applicators #1244/1245. Apply paint 3 to 4 inches from surface as a writing tool, and 5 to 8 inches in the applicator for a $\frac{3}{4}$ -inch line or continuous directional mark. Keep can in motion during use to prevent puddling. Agitate can periodically during application. Clear paint from valve and tip after each use by turning can in an upright position and spraying for 3 to 5 seconds. For best results, use at temperatures between 60°F and 80°F (16°C to 27°C).

Limitations: Please refer to the Safety Data Sheets for specific information on material hazards, etc. This aerosol product is designed to spray at an angle not greater than 30° from vertical.

Packaging:

Aerosol:	Cans (16 oz.)	12 net wt. (340 g)	14.1 fl. oz. (417 ml)
	Case (12/case)	14 lbs. (6.35 kg)	0.47 CF (0.013 CM)

II. CHARACTERISTICS & PROPERTIES (Average for all colors)

Specifications:

These aerosols comply with CARB MIR requirements. Colors formulated to meet standards set by OSHA and APWA/One Call systems

Appearance:

	Regular	Fluorescent
Gloss at 60°	<5	<5
Class	Flat	Flat

Coverage:

Typical	390 linear ft./can	400 linear ft./can
---------------	--------------------------	--------------------

Drying Schedule: (At 77°F [25°C], 50% Humidity at 1 mil, dry)

To touch	30 min	30 min.
To handle	45 min	45 min.
Full cure	8 hrs.	8 hrs.
To recoat	Not required	Not required

Performance and Chemical Properties:

Weight per gallon	7.46 lbs.	7.52 lbs.
Specific gravity	0.89	0.90
Viscosity	Not applicable	55 KU
Flammability: Label marking	Extremely flammable	Extremely Flammable
Flash point	<0 °F (-18°C)	<0°F (-18°C)
Operating temperature range	60° to 80°F (16° to 27°C)	60° to 80°F (16° to 27°C)
Percent solids by weight	13%	18%
Percent solids by volume	6%	9%
Percent pigment by volume	4.1%	5%
CARB MIR Limits (ground traffic/marketing coating)	<0.85	<0.85
Interior durability	Excellent	Excellent
Exterior durability	Good	Good
Temperature resistance	Not applicable	Not applicable
Color fastness	Good	Poor
Adhesion	Good	Good
Mineral spirits resistance	Fair	Poor
Gasoline resistance	Fair	Poor
Motor oil resistance	Good	Very Good

Base Materials

Resin system	Alkyd	Alkyd
Solvents (top two)	VM&P Naphtha, Hexane	VM&P Naphtha, Hexane
Propellant system	Hydrocarbon	Hydrocarbon

III. SHIPPING, STORAGE AND HEALTH

	Regular & Fluorescent
UN number	UN1950
Proper Shipping Description	Aerosols
Hazard Class	2
Packing Group	N/A
Limited Quantity	Yes
Warehouse storage level number	NFPA 30B Level 1
Storage temperature	50° to 120°F (10° to 49°C)
Shelf life	1 to 2 years

HMIS ratings

Health	1
Fire	3
Reactivity	1

IV. MISCELLANEOUS

The APWA/One Call color designation system is used to identify location and direction of underground cables and pipes for above-ground utility construction. OSHA color assignment is used for physical risk or hazard identification. Contains no Ozone Depleting Substances (O.D.S.). This product meets MIR and VOC requirements for the State of California.

Color	APWA/One Call	OSHA
Red	Electric	Danger, stop or location of fire protection equipment
Yellow	Gas, Oil	Caution and physical hazards
Blue	Water	Equipment being repaired. Caution against starting or moving
Green	Sewer	Location of safety equipment other than fire
Orange	Communication, CATV	Dangerous parts of machinery or energized equipment
Purple	Reclaimed water	Radiation hazard
Black/White	White: Proposed excavation	Black/White: Traffic and housekeeping

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.