

# **CHOOSE YOUR OPTIONS**

## **SPECIFICATIONS** Stylist **U-Factor** Not Tested 6063-T Aluminum Frame Thickness 2 inches ½ inch insulated Glass 1/4 inch non-insulated 1/8 inch non-insulated Panel Rails Insulated non-insulated Air Infiltration Seal

5 years

Stylist Cross Section\* \*Pictured with optional insulation

Warranty\* Excludes Springs

\*For full warranty details contact your Midland dealer

1/2 inch tempered insulated glass 3/4 inch tempered insulated glass

# **FRAME COLORS**







Clear Anodized

Deep Bronze Anodized



Anodized






\*Printed colors may not be accurate. Contact your local Midland dealer for exact color samples

### STYLIST LITE


Doors up to 7' 2" wide = 1 panel

Doors 7' 3" to 12' 2" wide = 2 panels





Doors 12' 3" to 18' 2" wide = 3 panels




#### STYLIST XL

Doors up to 10' 2" wide = 1 panel

Doors 10' 3" to 18' 2" wide = 2 panels







Polystyrene insulation\*

Cross linked polyethylene\* \*Optional

Air infiltration seal provides an energy efficient seal to help maintain building temperature

#### **GLASS**





Plain

Satin Stylist