


# FULLVIEW & STYLIST



# CHOOSE YOUR OPTIONS

SPECIFICATIONS	Stylist	FullView Glass Panel	FullView Anodized Aluminum Panel
<b>U-Factor</b>	Not Tested	<b>0.85</b> 	Not Tested
Frame	6063-T Aluminum	6063-T Aluminum	6063-T Aluminum
Thickness	2 inches	2 inches	2 inches
Glass	½ inch insulated ¾ inch insulated	½ inch insulated ¼ inch non-insulated ⅝ inch non-insulated	—
Panel	—	—	½ inch insulated
Rails	Insulated non-insulated	Insulated non-insulated	Insulated non-insulated
Air Infiltration Seal	•	•	•

Warranty* Excludes Springs	5 years	5 years	5 years
----------------------------	---------	---------	---------

\*For full warranty details contact your Midland dealer



## FRAME COLORS



Color Select™

\*ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.

## GLASS



Plain\*



Obscure



Satin\*\*



Gray Tinted



Bronze



Low E




Double Dark\*

\*Stylist is only available in Plain & Satin Stylist.

\*\*Tempered only. All other glass is available in both tempered and untempered.

## TRACK CONFIGURATIONS



**Standard Lift**  
For normal installations




**Inclined Track**  
To follow pitch of roof



**Hi-Lift**  
To put horizontal track as close to ceiling as possible



**Vertical Lift**  
Full vertical rise where headroom is available



**Low Headroom**  
For low-clearance installations