

SS4179

SAFETY DATA SHEET

1. Identification

Product identifier: SS4179

Other means of identification

Synonyms: Primer solution

Recommended use and restriction on use

Recommended use: Primer

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information : Momentive Performance Materials LLC
260 Hudson River Road
Waterford NY 12188

Contact person : commercial.services@momentive.com

Telephone : General information
+1-800-295-2392

Emergency telephone number

Supplier : CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 2

Health Hazards

Acute toxicity (Oral) Category 4
Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Specific Target Organ Toxicity - Single Exposure Category 2
Specific Target Organ Toxicity - Single Exposure Category 3¹.

Target Organs

1. Narcotic effect.

Label Elements

Hazard Symbol:

SDS_US

SS4179



Signal Word: Danger

Hazard Statement: H225; Highly flammable liquid and vapor.
H302; Harmful if swallowed.
H319; Causes serious eye irritation.
H317; May cause an allergic skin reaction.
H371; May cause damage to organs.
H336; May cause drowsiness or dizziness.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or if you feel unwell: Call a POISON CENTER or doctor. In case of fire: Use alcohol resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

SS4179

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
ETHYL ACETATE	141-78-6	50 - <100%	# This substance has workplace exposure limit(s).
Methyl Methacrylate	80-62-6	5 - <10%	# This substance has workplace exposure limit(s).
Methanol	67-56-1	3 - <5%	# This substance has workplace exposure limit(s).
DIBENZOYL PEROXIDE	94-36-0	0.1 - <1%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Do NOT induce vomiting.
Inhalation:	Move to fresh air.
Skin Contact:	Wash the skin immediately with soap and water. Wash contaminated clothing before reuse. Get medical attention if irritation persists after washing.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Most important symptoms/effects, acute and delayed

Symptoms: Itching Redness Pain Rash

Hazards: This product is not expected to produce adverse effects under normal conditions of use and appropriate personal hygiene.

Indication of immediate medical attention and special treatment needed

Treatment: Treatment is symptomatic and supportive.

5. Fire-fighting measures

SS4179

General Fire Hazards: Do not use water jet as an extinguisher, as this will spread the fire. Use water spray to keep fire-exposed containers cool.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Alcohol resistant foam. Carbon dioxide Dry chemical.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Ground container and transfer equipment to eliminate static electric sparks. In case of fire, gives off (emits): Carbon oxides

Special protective equipment and precautions for firefighters

Special fire fighting procedures: Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Product may charge electrostatically during pouring or filling. All equipment used when handling the product must be grounded.

Special protective equipment for fire-fighters: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Avoid contact with eyes, skin, and clothing. Keep out of reach of children. Attention: Not for injection into humans.

Methods and material for containment and cleaning up: Warn other workers of spill. Wear proper protective equipment as specified in the protective equipment section. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal.

Notification Procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

SS4179

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is expected; material has a flash point below 200 F. Do not get in eyes, on skin, on clothing. Do not taste or swallow. Use only in well-ventilated areas. Wash thoroughly after handling. Product may charge electrostatically during pouring or filling. All equipment used when handling the product must be grounded. See Section 8 of the SDS for Personal Protective Equipment.

Conditions for safe storage, including any incompatibilities: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
ETHYL ACETATE	TWA	400 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	400 ppm 1,400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	400 ppm 1,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	400 ppm 1,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	400 ppm 1,400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	TWA PEL	400 ppm 1,400 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	LEL	2.0 %	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	IDLH	2,000 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	ST ESL	3,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	870 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
Methyl Methacrylate	AN ESL	400 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	1,440 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	TWA	50 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	100 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	100 ppm 410 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	100 ppm 410 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000),

SS4179

			as amended (1989)
	TWA	100 ppm 410 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	TWA PEL	50 ppm 205 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	STEL	100 ppm 410 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	IDLH	1,000 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	AN ESL	50 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	210 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	210 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	860 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
Methanol	TWA	200 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	250 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	250 ppm 325 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2010)
	REL	200 ppm 260 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	200 ppm 260 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	200 ppm 260 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	250 ppm 325 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	200 ppm 260 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	TWA PEL	200 ppm 260 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	Ceiling	1,000 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	STEL	250 ppm 325 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	IDLH	6,000 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	STEL	250 ppm 325 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
	AN ESL	2,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	1,600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	3,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)

SS4179

DIBENZOYL PEROXIDE	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
DIBENZOYL PEROXIDE - Particulate.	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
DIBENZOYL PEROXIDE	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	IDLH	1,500 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Methanol (methanol: Sampling time: End of shift.)	15 mg/l (Urine)	ACGIH BEI (03 2015)

Appropriate Engineering Controls

Provide eyewash station and safety shower. If the formation of aerosol/mist cannot be excluded, ensure effective exhaust ventilation in the working area.

Individual protection measures, such as personal protective equipment

General information:	Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.
Eye/face protection:	Face shield Monogoggles
Skin Protection	
Hand Protection:	Rubber or plastics gloves
Other:	Wear suitable protective clothing and eye/face protection.
Respiratory Protection:	If inhalation exposure is expected, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).
Hygiene measures:	Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid contact with eyes, skin, and clothing. Do not eat, drink or smoke when using the product.

SS4179

9. Physical and chemical properties**Appearance**

Physical state: liquid
Form: liquid
Color: Colorless

Odor: ester like

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: < 0 °C

Initial boiling point and boiling range: ca. 80 °C

Flash Point: -2.80 °C (Tagliabue Closed Cup)

Evaporation rate: ca. 6

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 11 %(V)

Flammability limit - lower (%): 2 %(V)

Explosive limit - upper: No data available.

Explosive limit - lower: No data available.

Heat of combustion: No data available.

Vapor pressure: Not applicable

Vapor density: No data available.

Density: ca. 0.91 g/cm³

Relative density: 0.91

Solubility(ies)

Solubility in water: Insoluble

Solubility (other): SOLUBLE IN ALCOHOLS

Partition coefficient (n-octanol/water) Log

Pow:

Auto-ignition temperature: ca. 385 °C

Decomposition temperature: No data available.

SADT: No data available.

Viscosity, dynamic: No data available.

Viscosity, kinematic: No data available.

Other information

Minimum ignition temperature: 385 °C

VOC: 859 g/l ;

SS4179

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	Keep away from sources of ignition - No smoking.
Incompatible Materials:	Oxidizing agents.
Hazardous Decomposition Products:	Methanol Formaldehyde. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix: 1,941.1 mg/kg
----------------------	-----------------------

SS4179

Specified substance(s):

ETHYL ACETATE	LD 50 (Rat, No data available.): 5,620 mg/kg LD 50 (Guinea Pig, No data available.): 5,500 mg/kg LD 50 (Mouse, No data available.): 4,100 mg/kg LD 50 (Rabbit, No data available.): 4,935 mg/kg
---------------	--

Methyl Methacrylate	LD 50 (Rat): 7,872 mg/kg
---------------------	--------------------------

DIBENZOYL PEROXIDE	LD 50 (Rat): 6,400 mg/kg
--------------------	--------------------------

Dermal

Product:	ATEmix: 10,000 mg/kg
-----------------	----------------------

Specified substance(s):

ETHYL ACETATE	LD 50 (Rabbit,): 20,000 mg/kg
---------------	--------------------------------

Inhalation

Product:	ATEmix: 100 mg/l
-----------------	------------------

Repeated dose toxicity

Product:	No data available.
-----------------	--------------------

Skin Corrosion/Irritation

Product:	No data available.
-----------------	--------------------

Serious Eye Damage/Eye Irritation

Product:	No data available.
-----------------	--------------------

Respiratory or Skin Sensitization

Product:	No data available.
-----------------	--------------------

Carcinogenicity

Product:	No data available.
-----------------	--------------------

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

SS4179

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Target Organs
Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
ETHYL ACETATE LC50 (Leuciscus idus, 48 h): ca. 270 mg/l
LC50 (Pimephales promelas, 96 h): 230 mg/l

Methanol LC50 (Pimephales promelas, 96 h): 28,100 mg/l

Aquatic Invertebrates
Product: No data available.

Specified substance(s):
ETHYL ACETATE LC0 (Daphnia magna): 1,562 mg/l
(Daphnia magna): 3,090 mg/l

Chronic hazards to the aquatic environment:

SS4179

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

ETHYL ACETATE 68 % (5 d)
85 % (28 d)

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

ETHYL ACETATE No data available.
Methyl Methacrylate No data available.
Methanol No data available.
DIBENZOYL PEROXIDE No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Disposal should be made in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of as unused product.

SS4179

14. Transport information

DOT

UN Number:	UN 1993
UN Proper Shipping Name:	Flammable liquids, n.o.s.(ETHYL ACETATE, METHANOL)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
Packing Group:	II
Marine Pollutant:	No

IMDG

UN Number:	UN 1993
UN Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S.(ETHYL ACETATE, METHANOL)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
EmS No.:	F-E, S-E
Packing Group:	II
Marine Pollutant:	No
Limited quantity	1.00L
Excepted quantity	E2

IATA

UN Number:	UN 1993
Proper Shipping Name:	Flammable liquid, n.o.s.(ETHYL ACETATE, METHANOL)
Transport Hazard Class(es):	
Class:	3
Label(s):	3
Packing Group:	II
Cargo aircraft only Packing Instructions:	364
Passenger and cargo aircraft Packing Instructions:	364
Limited quantity:	Y341
Packing Instructions:	
Excepted quantity	E2
Environmental Hazards:	Not regulated.
Marine Pollutant:	No

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

SS4179

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
ETHYL ACETATE	Causes mild skin irritation.; Systemic effects
Methyl Methacrylate	Skin sensitizer; Respiratory hazard.
Methanol	Toxic by ingestion; Toxic by skin absorption; Systemic effects
gamma-Methacryloxypropyltrimethoxysilane	Causes mild skin irritation.; Respiratory hazard.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
ETHYL ACETATE	5,000 lbs.
Methyl Methacrylate	1,000 lbs.
Methanol	5,000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Serious eye damage or eye irritation
Respiratory or Skin Sensitization
Specific target organ toxicity (single or repeated exposure)
Hazards Not Otherwise Classified (HNOC)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
--------------------------	------------------------------------

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Methyl Methacrylate		
Methanol		

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
--------------------------	----------------------------

SS4179

Methyl Methacrylate Reportable quantity: 1,000 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including Methanol, which is [are] known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

ETHYL ACETATE

Methyl Methacrylate

Methanol

gamma-Methacryloxypropyltrimethoxysilane

DIBENZOYL PEROXIDE

US. Massachusetts RTK - Substance List

Chemical Identity

ETHYL ACETATE

Methyl Methacrylate

Methanol

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

ETHYL ACETATE

Methyl Methacrylate

Methanol

US. Rhode Island RTK

Chemical Identity

ETHYL ACETATE

Methyl Methacrylate

Methanol

SS4179

Inventory Status:

Australia AICS:	y (positive listing)	Remarks: None.
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	y (positive listing)	Remarks: None.
China Inventory of Existing Chemical Substances:	y (positive listing)	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	Please contact your supplier for further information on the inventory status of this material.	Remarks: Toxic substance
Canada NDSL Inventory:	n (negative listing)	Remarks: None.
Philippines PICCS:	y (positive listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: None.
New Zealand Inventory of Chemicals:	y (positive listing)	Remarks: None.
Taiwan. Taiwan inventory (CSNN):	y (positive listing)	Remarks: None.
REACH:	If purchased from Momentive Performance Materials GmbH in Leverkusen, Germany, all substances in this product have been registered by Momentive Performance Materials GmbH or upstream in our supply chain or are exempt from registration under Regulation (EC) No 1907/2006 (REACH). For polymers, this includes the constituent monomers and other reactants.	Remarks: None.

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	<input type="text" value="3"/>
Flammability	<input type="text" value="3"/>
Physical Hazards	<input type="text" value="0"/>
PERSONAL PROTECTION	<input type="text"/>

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 05/28/2021

Revision Date: No data available.

Version #: 3.1

SS4179

Further Information: No data available.

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safehandling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

® and TM indicate trademarks owned by or licensed to Momentive.