## FEEDTECH UNDER & OVER ROLLER MILLS









**Feedtech** offer a range of **Under & Over Roller Mills to** suit most feeding systems.



## **FEATURES:**

Fully automatic and manually operated roller mills are available in three sizes:

4" (Rolls 4" W x 8" Diam.) Capacity = 1.50 Tonne per hour 6" (Rolls 6" W x 8" Diam.) Capacity = 2.50 Tonne per hour 8" (Rolls 8" W x 8" Diam.) Capacity = 4.00 Tonne per hour

Note: Specified Roller Mill capacity can vary according to type and condition of grain.

## **FEATURES:**

- 5 hp Electric Motor (4" Mills)
- 10 hp Electric Motor (8" Mills) Solid rollers
- Belt & Gear drive combination Magnetic protection of rollers

- Robust M/S construction
- 10 hp Electric Motor (6" Mills)

- Spring loaded roller overrides Quick & simple adjustment of rollers
  - · Remote lubrication of bearings
- Fully guarded, preventing accidental access to moving parts

- Fully Automatic Digital Controller Manual Controller
- 3 Phase or Single phase
- Overhead hopper with external choke or with mill lid slide to control grain flow
- · A conversion kit can be fitted to existing Mill to make an older single Mill into an under and over Mill
- 12 Month Warranty
- Australian Made

www.feedtech.com.au

(03) 5824 1466 • sales@treveng.com.au