









# Series 2051 Stucco Replacement Garden Window

Designed specifically for stucco remodeling applications, the Series 2051 garden window installs like a new construction window.











#### Please Note:

\*Although units of a larger size do not have the same R-50 "Coastal Rating," they still provide all of the features and options of the smaller sizes.

The color samples shown here are reproduced by mechanical process and may vary from actual colors of the product. Please contact your sales representative for samples before ordering.

### Ventana USA

6001 Enterprise Drive Export PA 15632-8969

Phone: 724.325.3400 Fax: 724.327.4540 www.ventana-usa.com information@ventanapa.com It incorporates aluminum nail flanges for mounting directly to the outside of the existing window framing (knee braces are required for support). The sill flange can be mounted prior to window placement which aids installation of the unit. A major advantage of this design is that there is no disruption to the interior wall treatment.

#### Structural Features

- ➤ The Series 2051 stucco replacement garden window has an AAMA Certified R-50 rating for units 60.5 x 60.5 inches and smaller.\*
- Fully welded, rigid PVC vinyl frame for greater strength and stability.
- > Aluminum and steel reinforcements in the front mullion.
- ➤ Vinyl frame will not chip, rot, or peel and will never need to be painted.
- Clear 1-inch insulated glass package.
- ➤ Top sloped insulating glass (a constant 35-degree pitch) is tempered for improved safety and unit integrity.
- ➤ The projection of the window from the exterior wall face is a constant 17 inches.
- Both vents and deadlites have a built-in weep system and external glazing.
- ➤ A two-part structural silicone is used to glaze the top slope and vertical deadlite portions of the unit.
- ➤ Snap-in sill cover for seat board provides aesthetic appeal and weather resistance.
- > Snap-in corner slope closure profile assures a tight weather seal.
- ➤ Exterior grade plywood seat board, is 1-1/4-inch for improved structural and thermal performance.
- > The window is shipped completely assembled for easy installation.

## **Operating Sash**

- Locks and operators are mounted to the inside front area for easy access.
- Operators are sealed to prevent air and water infiltration.
- ➤ Twin sealing, fully screened, operating casements with external glazing for improved weather protection.
- ➤ The multi-point locking system provides a tighter seal and added security.

#### **Colors and Options**

➤ Head board, seat board and jamb are available in Birch, Oak and White or Tan high-pressure laminate.



➤ Standard frame colors are white and tan. Other colors are available by special order, including: Champagne or Cocoa exterior with a White interior and White exterior with a Light Oak laminate interior.



➤ Acrylic solid seatboard inserts are available in White, Tan, Vanilla Sugar, Gray Granite, Black Pearl or White Quartz.



- ➤ Highly recommended: Insulation board with an "R" value of 5 can be installed under the seat board to increase the "R" value to 6.22. This 1-inch thick lightweight rigid material is 100 percent waterproof.
- ➤ One or more adjustable glass shelves with polished edges, brackets and standards. Depending upon the width of the unit, the glass thickness will be either 3/8-inch or 1/2-inch.

