

Amor Classic



110
Winters
Oak



150
Sand Cliff
Oak



185
Dark Brown
Oak



300
Classic
Oak



350
Rural
Oak



510
Rustic
Oak



540
Sahara
Oak



580
Ancient
Oak



710
Silver Grey
Oak



720
Slate Grey
Oak



730
Grayson
Oak



750
Midnight
Oak

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice. *Subject to proper installation and maintenance.

Amor Classic

Amor Classic not only harnesses the stylistic nature of timber, these practical laminate planks also have a waterproof^ surface meaning you won't need to worry about a spilled drink or muddy shoes on your floor. Create a modern looking interior space, with the peace of mind that your floor will stand up to everyday life.

Technical Data

Type	Laminate	Country of Origin	Belgium
Plank Thickness	8mm	Finish	Matte
Dimensions	1200mm (L) x 190mm (W)	Surface	Embossed
Planks per Box	7	Substrate Layer	850kg/m³ High Density Fibreboard
M² per Box	1.596m²	Backing Layer	Balancing Layer
M² per Pallet	95.76m²	Profile	Pressed Bevel
Colours	12		
Installation Method	Unifit®		

Performance

Domestic Classification	23 - Heavy Use Applications	EN1329
Commercial Classification	32 - Moderate Use Applications	EN1329
Static Indentation	≤0.05mm	EN433
Abrasion Rating	AC4 - Heavy Domestic Use / Moderate Commercial Use	EN 13329
E3 Internal Moisture	Wet Areas use - Kitchen, Bathroom, Toilet, Powder Room, Laundry	E3/AS1* *Must be installed in accordance with Godfrey Hirst installation instructions.
Impact Sound Reduction	Ln,W 55 IIC 54	ISO10140-3 ASTM E492-09
Light Fastness	Class 8 – Blue Reference	EN ISO 105-BO2
Fire Classification	CRF 6.1 kW/m² Smoke Value 11%.min	AS/ISO 9239
Slip Resistance	P2	AS/NZ 4586-2013

Sustainability

VOC Rating	CETEC Compliant for VOC Emission Rate Limits
------------	--

