

## Laminate

# **Astoria**





White Iris



<sup>130</sup> Silver Lilly



<sup>190</sup> **Dakota** 



<sup>330</sup> Isla Rose



Summer Grace



540 **Rata** 



Nina May



715 **Harper** 



June Mist



795 **Trinity** 

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice. "Subject to proper installation and maintenance.



### Laminate

## **Astoria**

Offering a unique variety of grain patterns and hues, Astoria is the perfect floor for your home decor. Astoria is a stylish Laminate that makes a charismatic and durable flooring statement. The distinctive natural grain is highlighted with an embossed in register finish for an authentic timber appearance.

#### **Technical Data**

Туре	Laminate
Plank Thickness	8mm
Dimensions	1200mm (L) x 190mm (W)
Planks per Box	7
M² per Box	1.596m <sup>2</sup>
M² per Pallet	95.76m <sup>2</sup>
Colours	10
Installation Method	Unifit®

Country of Origin	Belgium
Finish	Matte
Surface	Emboss in Register
Substrate Layer	850kg/m³ High Density Fibreboard
Backing Layer	Balancing Layer
Profile	Square Edge

#### **Performance**

Domestic Classification	23 - Heavy Use Applications	EN1329
Commercial Classification	32 - Moderate Use Applications	EN1329
Static Indentation	≤0.05mm	EN433
Abrasion Rating	AC4 - Heavy Domestic Use / Moderate Commercial Use	EN 13329
E3 Internal Moisture	Wet Areas use - Kitchen, Powder Room, Laundry	E3/AS1* *Must be installed in accordance with Godfrey Hirstinstallation instructions.
Light Fastness	Class 8 - Blue Reference	EN ISO 105-BO2
Fire Classification	CRF 6.1 kW/m <sup>2</sup> Smoke Value 11%.min	AS/ISO 9239
Slip Resistance	R9/P1	AS/NZ 4586-2013

### Sustainability

VOC Rating	CETEC Compliant for VOC Emission Rate Limits













