



Belle XL



110
Salt Lake
Oak



180
Woodstock
Oak



320
Husk
Oak



350
Taylor
Oak



500
Nordic
Oak



520
Coastal
Oak



540
Driftwood
Oak



550
Desert
Oak



580
Castlerock
Oak



710
Sterling
Oak



730
Misty
Oak



750
Raven
Oak

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice. *Subject to proper installation and maintenance.

Belle XL

Accentuate the grand space in a room with the ultimate in elegant style and affordability. Belle XL laminate planks are not only extra wide at 240mm, but each plank is an incredible 2050mm long allowing you to create stunning interior style with a practical laminate floor.

Technical Data

Type	Laminate	Country of Origin	Belgium
Plank Thickness	8mm	Finish	Soft Touch Matte
Dimensions	2050mm (L) x 240mm (W)	Surface	Embossed
Planks per Box	7	Substrate Layer	850kg/m ³ High Density Fibreboard
M ² per Box	3.444m ²	Backing Layer	Balancing Layer
M ² per Pallet	113.652m ²	Profile	Micro Bevel
Colours	12		
Installation Method	FitXpress®		

Performance

Domestic Classification	23 - Heavy Use Applications	EN1329
Commercial Classification	32 - Moderate Use Applications	EN1329
Static Indentation	≤0.05mm	EN433
Abrasion Rating	AC4 - Heavy Domestic Use / Moderate Commercial Use	EN 13329
E3 Internal Moisture	Wet Areas use - Kitchen, Powder Room, Laundry	E3/AS1* <small>*Must be installed in accordance with Godfrey Hirst installation instructions.</small>
Impact Sound Reduction	Ln,W 55 IIC 54	ISO10140-3 ASTM E492-09
Light Fastness	110 Salt Lake Oak 38.46% 350 Taylor Oak 16.33% 580 Castlerock Oak 16.44% 790 Raven Oak 10.36%	180 Woodstock Oak 11.66% 500 Nordic Oak 26.53% 710 Sterling Oak 34.05% 540 Driftwood 26.3% 320 Husk Oak 22.89% 520 Coastal Oak 26.57% 730 Misty Oak 20.52% 550 Desert Oak 19.34%
Fire Classification	CRF 6.1 kW/m ² Smoke Value 11%.min	AS/ISO 9239
Slip Resistance	R10/P3	AS/NZ 4586-2013

Sustainability

VOC Rating	CETEC Compliant for VOC Emission Rate Limits
------------	--

