



# Oak Elegance 190



180  
**Coffee**  
Oak



300  
**Natural**  
Oak Smooth



360  
**Rustic**  
Oak



510  
**Coastal**  
Oak



560  
**Weathered**  
Oak



530  
**Cinnamon**  
Oak



710  
**Ashen**  
Oak

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice. \*Subject to proper installation and maintenance.

# Oak Elegance 190

With a real European Oak surface, Oak Elegance 190 provides a unique look for your home with true-to-life distinct knots and grain variation. The contemporary range of colours are all Medium Feature Grade, which offers a clean yet distinctive character in every board and every floor. Finished with a high quality German lacquer and a light brush veneer, Oak Elegance 190 has the timeless look and feel of luxury.

## Technical Data

Type	Engineered Timber	Colours	6
Board Thickness	14mm	Finish	Matte Finish with very light brush
Veneer Thickness	3mm	Surface	French Oak Veneer (3mm)
Dimensions	1900mm (L) x 190mm (W)	Substrate Layer	Poplar
Boards per Box	6 Boards Equivalent* 16% Nested/Random Lengths	Core & Backing Layer	Eucalyptus/Poplar Multiply
M <sup>2</sup> per Box	2.166m <sup>2</sup>	Profile	Micro Bevel Edge
M <sup>2</sup> per Pallet	108.3m <sup>2</sup>		
Installation Method	5G InstaClic®		

## Performance

Coating System	UV Cured Lacquer	ISO 00000
Moisture Content	8-11% (+/- 2%) at time of delivery	EN 13183-1
Impact Sound Reduction	Ln,W 56 IIC 55	ISO 10140-3 ASTM E492-09
Fire Classification	CHF 3.8kW/m <sup>2</sup> Smoke Value 17%.min	AS/ISO 9239
Slip Resistance	P2 - 300 Natural Oak Smooth P4 - All other colours	AS/NZ 4586 - 2013
Warranty†	Consumer Guarantee	
Recommended Adhesive	Refer Godfrey Hirst Adhesive Recommendation Guide	

## Sustainability

Indoor Air Quality	Green Building Council compliant for VOC emission rate limits
--------------------	---

