

Metropol 1500



100
Alabaster



180
Burnt Umber



300
Sable Oak



500
Cornsilk



520
Brass Oak



545
Apple-Box Gum



555
Marble Spotted Gum



560
Burl Oak



580
Fallow Oak



700
Platinum Grey



720
Pepper Oak



790
Silhouette Oak



While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice. *Subject to proper installation, maintenance and local building code/regulatory approval.

Metropol 1500

Delivering super durable and impact resistant flooring with exquisite design, Metropol 1500 is a technologically advanced hybrid range that ticks all the right boxes. Available in a wide range of natural timber hues, your next project is a guaranteed winner with strong, stable and beautiful flooring that's easy to install.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.5mm	Surface	Embossed
Wear Layer	0.5mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1500mm (L) x 228mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm IXPE
M² per Box	2.05m²	Profile	Micro Bevel
M² per Pallet	123.12m²	Protective Coating	PUR
Colours	12		
Installation Method	Uniclic®		

Performance

Dimensional Stability	Length: 0.0 Width: 0.0 Curling 0.0	ISO23999
Thermal Resistance	0.039m² K/w	ISO 8301
Thermal Conductivity	0.128 W/(m.K)	ISO 8301
Abrasion Rating	Group T	EN 660-2
Swelling After Submersion in Water	Result is 0.1%	ISO 24336
Impact Sound Reduction	TBA	ISO 10140-3, ASTM E492-09
Light Fastness	≥6	EN ISO 105-B02
Light Reflectance Values	100 Alabaster 46.14 % 500 Cornsilk 30.04% 555 Marble Spotted Gum 12.32% 700 Platinum Grey 33.98%	180 Burnt Umber 8.60% 520 Brass Oak 22.30% 560 Burl Oak 11.41% 720 Pepper Oak 19.10%
Fire Classification	CRF 11.1 kW/m² Smoke Value 210% min	ISO 9239
Slip Resistance	P3	AS/NZ 4586 - 2013

Sustainability

Indoor Air Quality	Green Building Council compliant for VOC emission rate limits
---------------------------	---



All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Hybrid Plank products must be installed in accordance with relevant New Zealand Standards and in conjunction with the Godfrey Hirst Floors Hybrid Plank Installation Instructions.
†Warranty terms and conditions apply. Test results and certificates are available on request.