

## Vinyl Plank

# Avvio 🕦







100 Voile 22110



**Batik** 22256



150 Lantana 22262



720 **Batiste** 22290



300 Linen 22301



350 Camile 22311



500 **Moire** 22360



550 **Camlet** 22565Q



160 Cerville 22830



180 Viyella 22892Q



**Octavius** 22949Q



750 **Barathea** 22950

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed. Please notes some colours in this range (as noted above and on front of samples) have a visual design effect that results in tonal variations amid the boards for a natural timber look. Please seek to view larger samples and consult with your retailer for further advice. "Subject to proper installation and maintenance.



### **Vinyl Plank**

## **Avvio**



Avvio vinyl plank flooring combines excellent durability with great style and performance. Perfect for every area of your home Avvio is 100% Waterproof, easy to maintain and stain resistant.

#### **Technical Data**

| Туре                | Vinyl Plank            |
|---------------------|------------------------|
| Plank Thickness     | 2mm                    |
| Wear Layer          | 0.3mm                  |
| Dimensions          | 1320mm (L) x 196mm (W) |
| Planks per Box      | 18                     |
| Colours             | 12                     |
| Installation Method | Direct Stick           |

| M² per Box         | 4.66m <sup>2</sup> |
|--------------------|--------------------|
| M² per Pallet      | 260.79m²           |
| Finish             | Matte              |
| Surface            | Embossed           |
| Profile            | Micro Bevel        |
| Protective Coating | Superguard™        |

### **Performance**

| Classification                         | 23, 31   | ISO 10874      |
|--|--|----------------|
| Dimensional Stability                  | Length: 0.05%<br>Width: 0.05%<br>Curling: 0.00%            | ISO 23999      |
| Abrasion Rating                        | Group T  | EN ISO 660-2   |
| Residual Indentation                   | <0.1mm   | ISO 24343-1    |
| Castor Chair                           | No Damage  | ISO 4918       |
| Impact Sound Reduction<br>Direct Stick | 4dB  | EN ISO 717-2   |
| Light Fastness                         | ≥ 6  | EN ISO 105-B02 |
| Reaction to Fire                       | CRF 10.4Kw/m²<br>Smoke Value 100% Minutes without U/Lay    | AS ISO 9239.1  |
|  | CRF 9.3Kw/m²<br>Smoke Value 141% Minutes with U/Lay        | AS ISO 9239.1  |
| Slip Resistance                        | R9 / P3  | AS/NZ 4586     |
| Suitable for wet areas                 | Yes - subject to proper installation and maintenance       |                |
| Recommended Adhesive                   | Refer to Godfrey Hirst Adhesive Guide www.godfreyhirst.com |                |

### Sustainability

| VOC Rating    | Passes CETEC VOC test  |
|---------------|--|
| Accreditation | Manufactured under a management system certified as complying with ISO 9001 & ISO14001 |













