### **POWER UNITS**

# **6BGIT**

**SPECIFICATION** 



Isuzu Power Solutions. For those who never stop.











## AT A GLANCE

**Power Output** ■ Max. 121.6 kW / 163.1 hp

(rated) @ 2200 RPM Max. 103.4 kW / 138.6 hp

(cont.) @ 2200 RPM

Torque Output ■ Max. 554 Nm @ 1800 RPM

**Displacement** ■ 6.5 L

Bore x Stroke ■ 105 x 125 mm

**O/A Dimensions** = 1201 mm (L) (engine only) = 572 mm (W) = 957 mm (H)

Dry Weight (engine only) ■ 490 kg

**Features** 

■ Turbocharged diesel engine

lacksquare Mechanical direct injection fuel system

■ Low noise, low fuel consumption, low maintenance

■ Easy to start

■ Reliable power

■ Water cooled

■ Tier-2 emission spec. reference

■ Genuine Isuzu engine manufactured in Japan

#### RFORMANCE ENGINE **Engine Power** 1200 1400 2000 2200 1000 1600 1800 Rated (kW / hp) 56.0 / 75.1 70.0 / 93.9 88.0 / 118.0 104.4 / 140.0 115.0 / 154.2 121.6 / 163.1 45.0 / 60.3 Continuous (kW / hp) 38.3 / 51.3 47.6 / 63.8 59.5 / 79.8 74.8 / 100.3 88.7 / 119.0 97.8 / 131.1 103.4 / 138.6



## **SPECIFICATIONS**

_	-		-

Туре:	Vertical water-cooled 4-cycle Diesel		
Model (Manufacturer):	6BG1-TRW02 (Isuzu)		
Emission Spec. Reference:	Tier-2 / Stage-II		
Max. Rated Output:	121.6 kW (163.1 hp) @ 2200 RPM		
Continuous Output:	103.4 kW (138.6 hp) @ 2200 RPM		
Max. Torque	554 Nm @ 1800 RPM		
Displacement:	6.5 L		
Combustion System:	Direct Injection (Turbocharged)		
O/A Dimensions:	1201 (L) x 572 (W) x 957 mm (H)		
Dry Weight:	490 kg		
Fuel Consumption:	36.0* L/h @ 100% load		
*Based on diesel fuel with a specific g	ravity of 0.835 kg/m3 at 15°C. Actual value may vary.		

#### **POWER UNIT CONFIGURATIONS**

#### 1. Starter (STR)

- Light duty air cleaner system
- Industrial grade exhaust system
- Engine mounting feet
- Heavy duty full aluminium cooling system (max. 45°C)
- 12V complete electrical system (incl. engine harness and stop solenoid)

#### 2. Economy (ECY)

#### Features include STR plus:

- Medium duty air cleaner system (dual element)
- Skid rail chassis mounting
- Mechanical vernier throttle kit
- IP65 'ECO' engine controller (essential watchdog protection)
- Engine RPM sender (MPU)

#### 3. Premium (PRM) Features include ECY plus:

- · Air cleaner restriction indicator
- Residential grade exhaust system
- High performance heavy duty cooling system (50°C +)
- Engine oil pressure and temperature senders
- IP65 'PRO' engine controller (advanced watchdog protection + application I/O)
- Remote oil drain kit

## KEY BENEFITS

#### DESIGN

Australian designed and sourced engine mounts and skid

Australian designed heavy duty bar and plate all aluminium radiator

Premium quality air cleaners

Complete electrical engine harness (includes engine stop solenoid, glow plug assisted start, fuel feed pump)

#### CONTROL PANEL

DeepSea 'ECO' economy engine controller (provides essential engine monitoring protection)

ComAp 'PRO' professional engine controller

(advanced engine monitoring protection, plus customer application inputs/outputs, complete event history log, large easy to read display)







ComAp 'PRO' Controller

#### OPTIONS

Premium pump pressure transducer range

Flywheel stub shafts

Auxiliary PTO crankshaft pulley

4G remote monitoring and control kit

Heat Exchanged cooling package Low coolant alarm protection kit

160W solar battery charging kit

Extension harnesses

Coolant surge tank kit



Transducer option



Heat Exchanger option



Clutch option