

MODIFIED ASPHALT PRIMER

Overview

Pro-Tech's Modified Asphalt Primer is an acrylic modified asphalt primer designed for use over various existing roofing substrates. This cost effective primer has outstanding adhesion characteristics.

Properties	Average Value
Viscosity	3000 CPS
Color	Black
Shelf Life	6 months
Elongation	Approximately 800%
Adhesion	Excellent
Film Integrity	Excellent
Flash Point	N/A
Weight per Gallon	9 lbs.

Note: The above values are average values obtained from a lab and should serve only as a guide.

Basic Use:

Modified Asphalt can be used over smooth or granulated build-up, modified bitumen, metal and single ply membranes as well as previously coated roofing substrates.

Packaging and Mixing:

Modified Asphalt Primer does not require thinning prior to use and is available in 5 gallon pails and 55 gallon drums. This product is available in black only. It is recommended to thoroughly mix all material prior to use, utilizing an appropriate mixing blade.

Installation

Modified Asphalt Primer can be spray applied using airless spray equipment, or a heavy nap roller or brushes for smaller areas. Spray application is the preferred method for application to achieve consistency and uniform film build. All surfaces shall be clean, dry and free of all dirt, grease, oil, and other surface contaminants that could interfere with proper adhesion to the roofing substrates.

Apply Modified Asphalt Primer at the maximum rate of 1/2-1 gallon per 100 sq. feet per gallon over smooth non-porous or previously coated surfaces. Modified Asphalt Primer shall always be applied at temperatures of 50 degrees and rising when weather conditions will permit drying before rain, dew or freezing temperatures occur.

Technical Services:

Additional information, product brochures and guide specification are available. Customized application instructions are also available from our technical experts.