

Siena Nylon Carpet Specifications: Canyon Broadloom

Style Name	Canyon Broadloom
Style Number	76
SPECIFICATIONS	
Construction	Textured Loop
Yarn Content	Zeftron SD Nylon
Dye Method	Solution
Machine Gauge	1/10in. (39.4col./10cm.)
Stitch Count	11 S.P.I.
Yarn Weight Tufted	23oz./yd.2
Pile Height	0.067"
Total Thickness	0.128"
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Recycled Content	N/A
Width	12 Feet (3.66m.)
Pattern Repeat	36" W x 33" L
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than .450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP2049
WARRANTIES	
Limited Warranty	10 Years Limited Warranty
ADDITIONAL INFORMATION	
Backing Options	Contact Sales
Custom Colors	Contact Sales
RECOMMENDED INSTALLATION(S)	



Siena Nylon Carpet Specifications: Canyon Tile

Style Name	Canyon Tile
Style Number	76T
SPECIFICATIONS	
Construction	Textured Loop
Yarn Content	Zeftron SD Nylon
Dye Method	Solution
Machine Gauge	1/10in. (39.4col./10cm.)
Stitch Count	12 S.P.I.
Yarn Weight Tufted	23oz./yd.2
Pile Height	0.067"
Total Thickness	0.128"
Primary Backing	Vinyl Compound
Secondary Backing	Vinyl Compound w/ Recycled Material
Recycled Content	N/A
Tile Size	24" W x 24" L
Pattern Repeat	N/A
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than .450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP2049
WARRANTIES	
Limited Warranty	10 Years Limited Warranty
ADDITIONAL INFORMATION	
Backing Options	Contact Sales
Custom Colors	Contact Sales
RECOMMENDED INSTALLATION(S)	
	1/4 Turn, Monolithic, Ashlar