



# HP-82

## HIGH PH TOUCHLESS PRESOAK

### DESCRIPTION

A medium-foaming presoak with a high concentration of alkali and surfactants that penetrate and release road-film, soil, oil, and grease from the vehicle surface.

### FEATURES

- Medium foaming formula
- Can be used in tunnel presoak arches
- ECOLOGO™ Certified

### APPLICATION

- Touchless
- APPROXIMATE USAGE: 32-80 ML/ APPLICATION\*
- Use proportioner tips (i.e. HydroMinder, Dema, etc.) in conjunction with downstream injection (i.e. Dema, venturi, etc.) to achieve final use dilution
- Use the high-pH presoak independently or in combination with a low-pH presoak to optimize cleaning.

### PACKAGING

5, 30 & 55 USG / 18.9, 114 & 208L

### SPECIFICATIONS

**Hyper-Concentrated**

**Appearance:** Clear blue, thin liquid

**Foam Color:** None

**pH:** 13-13.6

**SG:** 1.11

**DOT Labeling:** UN 3266, CLASS 8, PG III

**\*Approximate Number of Washes per 5 USG container:** 172-237

### TITRATION

Amount: 5ml

Reagent: 0.25N HCl

Dilution - Drops

35:1 - 20

50:1 - 14

65:1 - 11

80:1 - 9

95:1 - 7

110:1 - 6

125:1 - 6

REFER TO SAFETY DATA  
SHEET FOR EMERGENCY  
MEDICAL INFORMATION