



# HP-635

## LOW PH TOUCHLESS PRESOAK

### MODERATE TDS WATER

#### DESCRIPTION

A low-foaming, presoak with standard surfactant levels that effectively penetrate and remove dirt, oil, grease, bug residue, and road film from the vehicle surface when moderate TDS water is present.

#### FEATURES

- Unscented
- Moderate TDS Water
- Low foaming formula
- Formulated for use in challenging water conditions
- ECOLOGO™ Certified

#### APPLICATION

- Touchless
- APPROXIMATE USAGE: 30 ML/ APPLICATION\*
- Use proportioner tips (i.e. HydroMinder, Dema, etc.) in conjunction with downstream injection (i.e. Dema, venturi, etc.) to achieve final use dilution
- Use this presoak to prep and clean the vehicle surface before applying an alkaline-based presoak. Combining these products helps to overcome poor cleaning conditions.

#### PACKAGING

5 USG / 18.9L

#### SPECIFICATIONS

**Hyper-Concentrated**

**Appearance:** Clear, thin liquid

**Foam Color:** None

**pH:** 1-2

**SG:** 1.02

**DOT Labeling:** None (Non-Hazardous)

**\*Approximate Number of Washes per 5 USG container:** 631

#### TITRATION

Amount: 10ml

Reagent: 0.2N NaOH

Dilution - Drops

80:1 -	11
100:1 -	8
120:1 -	7
140:1 -	7
160:1 -	6
180:1 -	5
200:1 -	5
220:1 -	5
240:1 -	4

**REFER TO SAFETY DATA SHEET FOR EMERGENCY MEDICAL INFORMATION**