



TX-1

POWER SOAK

HIGH pH PRESOAK



DESCRIPTION

High Foaming, alkali-based detergent with mild solvents that quickly penetrates and removes heavy road-film, grease, and oil buildup on the vehicle surface.

FEATURES

- Safely loosens and removes oil, dirt, grease & road film from the vehicle's surface
- High foaming coverage
- Can be used as a stand alone presoak option, or in two step process
- can be used as a dual injection with an alkaline boost for more challenging road film
- safe to use on all vehicle surfaces

APPLICATION

- Friction, Rollover & Tunnel
- APPROXIMATE USAGE: 5-12 ML/ APPLICATION*
- Use proportioner tips (i.e. HydroMinder, Dema, etc.) in conjunction with downstream injection (i.e. Dema, venturi, etc.) to achieve final use dilution

! fl ~ /Z ~

2.5 & 5 USG / 9.45 & 18.9L

SPECIFICATIONS

Hyper-Concentrated

Appearance: Clear

Foam Color: None

pH: 8-9

SG: 1.08

DOT Labeling: UN 3266, CLASS 8, PG III

*Approximate Number of Washes per 5 USG container: 1577-3795

This product is compatible with



TITRATION

Amount: 10ml

Reagent: 0.2N NaOH

Dilution - Drops

35:1 - 48

50:1 - 25

75:1 - 20

100:1 - 18

130:1 - 11

170:1 - 8

200:1 - 4

300:1 - 7

400:1 - 5

500:1 - 4

REFER TO SAFETY DATA SHEET FOR EMERGENCY MEDICAL INFORMATION