

Delta TR

Temperature Rise
Rated Steel Doors

Delta TR

Enhanced fire protection for critical life safety requirements



Power Ready



STC 34*

- Full Size Closer Reinforcing
- Temperature Rise Rated Core
- Beveled Edges
- 7-Gauge Hinge Reinforcing
- 18-Gauge A60 Galvanneal
- Water-Based Primer Finish



Additional Options:

- Custom sizes and hardware configurations
- Flush top (steel top cap)
- Paintable galvanneal (unprimed) finish
- G90 galvanized steel
- Square edge/reversible
- Specialty finishes
- Window cutouts
- 16-Gauge A60 galvanneal steel

Complies with ANSI A250.8



Fire-Rated*

- Up to 3hr.
- Singles / Pairs



Hurricane*

- Up to +/- 90psf
- Singles / Pairs



Thermal Value

- R Value = 2.33
- U Value = 0.43

- △ Premium fire protection
- △ 450°F / 250°C temperature rise
- △ 10-year warranty

Performance Tested

Independently certified to meet the highest standards in performance for fire, severe weather and endurance testing, all backed by an unmatched factory warranty.

Hardware Compatibility

Compatible with all leading providers of security and access control systems, for both electrified and mechanical hardware.

Available Ratings

- 250°F at 30 minutes (US Standard)
- 450°F at 60 minutes (US Standard)
- 250°C at 60 minutes (Canadian Standard)

Applicable Standards:

- ANSI/BHMA A156.115
- ANSI A250.4
- ANSI A250.8
- ASTM A653
- ANSI A250.10
- UL 10B
- UL 10C
- ASTM E2010
- ASTM E2074
- CAN4 S104
- ASTM E90
- ASTM E413

*See specific listings for full details



DAYBAR

daybar.com
(888) 332-9227

architects@daybar.com
sales@daybar.com

DAYBAR
XPRESS