HIGH SPEED TABLE TOP

FOLDER

DF-850

Duplo's DF-850 is the fastest* table-top folding solution in it's category, with a top speed of 241 sheets per minute. It is twice as fast as its predecessors. User friendliness is at the heart of this folder with features such as easy to use control panel, batch mode, a reliable friction feeding mechanism and up & down counter. The efficency and productivity of the DF-850 results in both time and cost savings.



UNIQUE BUSINESS BENEFITS

- Up to 241 sheets per minute
- User friendly
- Paper sizes: B7 to A3
- Six pre-programmed popular folds
- Customise non-standard folds
- Crossfold as standard
- Batch mode
- Noise level: 76 dB *4

RECOMMENDED FOR

Who will benefit from adding a DF-850 to their workflow?

 Mailing houses, Governments, Councils, Publishers, Libraries, Local newspapers, Schools, Universities, Trade associations, Manufacturing, Hotels and leisure centres to mention a few.

Applications:

 Magazines & Newspaper inserts, Letters, Leaflets, Brochures, Menus, Bulletins and Direct mail pieces

7 FOLD TYPES















Single

Accordion

Gate

Irregular Accordion

Double

Letter

Cross-Fold





SPECIFICATIONS

	DF-850
Maximum Paper Size	297x432 mm
Minimum Paper Size	91x128 mm If the length of the sheet is less than 182mm- Only Single fold, Paper thickness: 64 to 81.4 g/m², affects exit stacking
Paper Quality	Recycled paper, Uncoated bond paper, Stencil paper, Art and coated paper*
Folding Mode	Single Fold, Double Fold, Irregular Accordion Fold, Letter Fold, Accordion Fold, Gate fold* ¹ ,cross fold* ² , custom fold* ³ .
Paper Weight	52.3 to 157 gsm
Maximum Processing Speed	241 sets/minutes A4, single fold , 81.4gsm
Capacity of Feeding Tray	500 sheets (fine quality paper 64 g/m²/17 lb.)
Feeding Mechanism	Manual up and down
Automatic Folding Stopper and Stacker Roller	No
Cross-Fold	Yes
Noise Level	76 dB*4
Power Supply	100-240 V (50/60 Hz)
Current Consumption	1.3-0.650 A (125 W)
Package Dimension	575x515x655 mm
Weight	31.5 kg

^{*}Art and coated paper - Subject to testing

Sound pressure level at peak: DF-850 - 99 dB & DF-870 - 94dB



Contact us 1800 422 349 ebusiness@smartech-aust.com www.smartech-aust.com



^{*}¹Gate Fold: Short grain paper less than 52.3gsm cannot be used

^{*2}Cross Fold: Fine quality paper 52.3 to 104.7gsm

^{*3}Custom Fold: Maximum finish length is 216mm

 $[\]ensuremath{^{*4}Noise}$ Level: Equivalent continuous A- weighted sound pressure level