



Belshe Industries, Inc  
 PO Box 626  
 Tecumseh, OK 74873  
 Phone (405) 273-1690  
 www.belshetrailers.com

<b>WB10</b>	<b>LIGHT &amp; MEDIUM HAUL</b>
-------------	--------------------------------

FEATURE TYPE	STANDARD MODEL FEATURES & MEASUREMENTS
<b>GVWR</b>	10,400 lbs.
<b>TRAILER WEIGHT (MIN)</b>	2,450 lbs.
<b>TRAILER DIMENSIONS</b>	
<b>Deck Length</b>	16 ft.
<b>Width Between Fenders</b>	76.5 in.
<b>Overall Width</b>	8 ft.
<b>Deck Height</b>	21.5 in.
<b>Fender Height</b>	10 in.
<b>Tongue Length</b>	32.5 in.
<b>Ramp Length</b>	5 ft.
<b>Overall Length</b>	20 ft.
<b>RUNNING GEAR</b>	
<b>Axles</b>	5,200 lbs. (x2)
<b>Brakes</b>	Electric
<b>Suspension</b>	5-Leaf 2 in. Slipper Spring
<b>Wheels</b>	15 in. 6-Bolt
<b>Tires</b>	15 in. Tires
<b>FRAME MATERIAL</b>	
<b>Outer Rails</b>	3 in. x 5 in. x 0.375 in. Angle A-36
<b>Cross Members</b>	3 in. x 4.1 lb. Channel A-36
<b>Tongue</b>	3.5 in. x 6 in. 0.375 in. Angle A-36
<b>Fender</b>	10 Gauge Formed
<b>LOADING CONFIGURATION</b>	
<b>Ramps</b>	5 ft. x 18 in. Ladder Bar Spring Assisted with Adjustable Width
<b>OTHER FEATURES</b>	
<b>Hitch</b>	2.5 in. Pintle Ring or 2 5/16 in. Ball 19 in. – 26 in. Adjustable
<b>Cargo Control</b>	D-Rings
<b>Flooring</b>	2 in. x 8 in. #1 Grade Treated Pine
<b>Jack</b>	12,000 lbs. Drop Leg
<b>Lighting</b>	LED, Sealed Wiring Harness
<b>Paint</b>	Primed, Acrylic Enamel – Black or Yellow Standard

**OPTIONAL UPGRADES**

- |          |             |                 |                    |
|----------|-------------|-----------------|--------------------|
| ✓ Length | ✓ Gooseneck | ✓ Cargo Control | ✓ Polyurea Coating |
| ✓ Width  | ✓ Decking   | ✓ Custom Color  |                    |