



Thermory® Hidden Fasteners and Screws



Quick Reference Guide

Features and Benefits:



- Stainless Steel clips with Stainless Steel screws
 - Silver 1/8" gap for 4" decking
 - Black 1/4" gap for 6" decking
 - Use 1 -40mm SIHGA Screw per clip
- Thermory® is equalized at 6% moisture content, so the clip system is designed to accommodate thermally modified material which can expand slightly, as opposed to tropical woods which can shrink dramatically
- Thermory® clip system sold in 45+ countries, so it performs in all climates
- The decking is of the highest quality and deserves the highest quality attachment system

✓ Durable and long lasting

Stainless Steel – strong 304 gauge lasts as long as the decking

✓ Air Movement

Holds decking up off the joists for air movement, which allows joist drying, lessens moisture transfer to the decking and reduces mold/mildew on joists which can lead to eventual joist rot

✓ Relieves stress on the wood

Resilient clip tabs allow expansion of material and absorbs the pressure, reducing cupping

SIHGA Screws®



✓ Self Tapping

✓ Stainless Steel

✓ Trim Head

40mm

- Use 1 screw per clip for face screwing decking and cladding, starter and end fastening, trim, stair risers and fascia with .79" thick (4/4) products

60mm

- Use for face screwing decking and cladding, starter and end fastening, porch flooring (both 4/4 and 5/4), trim, and stair treads
 - Predrill and counter bore screws within 3" of ends of decking boards and within 8" of ends of cladding
 - Stepped head and shaft auger promotes chip removal, reducing pressure and lessening splitting when sinking heads