

### **Tandem Disks**

Large producers and commercial operators want to cover a lot of ground in a hurry, and they can do just that with a Tandem Disk from Frontier Equipment. Large blades, deep penetration, and heavy-duty frames make even the largest projects manageable.

- Tapered roller gang bearings with oil bath lubrication
- Penetrates soil up to 9 in. (22.9 cm)
- 10.5 in. (26.7 cm) blade spacing
- 26 to 28 in. (66 to 71.1 cm) diameter disk blades (available in smooth, notched, or wavy)
- 265 to 370 lb. (120.2 to 167.8 kg) per blade

Model	Working Width	Drawbar HP	Hitch
TM5118	18 ft. (5.5 m) folding	180 hp (134 kW) Minimum	Cast link
TM5120	19 ft. 6 in. (6.1 m) folding	200 hp (149 kW) Minimum	Cast link
TM5121	21 ft. (6.4 m) folding	210 hp (157 kW) Minimum	Cast link
TM5124	23 ft. 6 in. (7.3 m) folding	220 hp (164 kW) minimum	Cast link
TM5129	29 ft. (8.8 m) folding	260 hp (194 kW) minimum	Cast link
TM5132	32 ft. (9.8 m) folding	280 hp (209 kW) minimum	Cast link



Why Vertical Tillage Might Be **Right For You** 



# **Vertical Tillage Tool**

The VT17 Series Vertical Tillage Tools provide speed, versatility, and performance to growers.

- Adjustable gang angles for desired aggressiveness
- Simple adjustments for increased uptime
- Rolling baskets and blade options provide the desired field finish

Model	<b>Working Width</b>	Engine HP	Hitch
VT1710	10.5 ft. (3.2 m)	85 - 105 hp (63.4 - 78.3 kW)	Pull-Type
VT1712	12 ft. (3.66 m)	95 - 120 hp (70.8 - 89.5 kW)	Pull-Type
VT1713	13 ft. (3.96 m)	105 - 130 hp (78.3 - 97.0 kW)	Pull-Type
VT1715	15 ft. (4.57 m)	120 - 150 hp (89.5 - 111.9 kW)	Pull-Type



### **3-Point Offset Disks**

Your land may be tough, but 3-Point Offset Disks are even tougher. As many as 24 notched disk blades enable you to level, cut, and mix soil to full working depth, all in one pass.

- High strength for adverse conditions
- Adjustable front and rear gang angles
- Optional adjustable blade scrapers for working in wet, sticky soil
- iMatch and/or Quick Hitch compatible

Model	Working Width	Engine HP	Hitch
DH3263	5 ft. 3 in. (1.6 m)	30 - 75 hp (22.4 - 55.9 kW)	Category 1 and 2
DH3272	6 ft. (1.8 m)	30 - 75 hp (22.4 - 55.9 kW)	Category 1 and 2
DH3280	6 ft. 8 in. (2.0 m)	30 - 75 hp (22.4 - 55.9 kW)	Category 1 and 2
DH3290	7 ft. 6 in. (2.3 m)	45 - 75 hp (33.6 - 55.9 kW)	Category 1 and 2
DH3299	8 ft. 4 in. (2.5 m)	45 - 75 hp (33.6 - 55.9 kW)	Category 1 and 2
DH3474	6 ft. 2 in. (1.9 m)	60 - 130 hp (44.7 - 96.9 kW)	Category 2 and 3
DH3480	6 ft. 8 in. (2.0 m)	60 - 130 hp (44.7 - 96.9 kW)	Category 2 and 3
DH3490	7 ft. 6 in. (2.3 m)	60 - 130 hp (44.7 - 96.9 kW)	Category 2 and 3
DH3499	8 ft. 4 in. (2.5 m)	60 - 130 hp (44.7 - 96.9 kW)	Category 2 and 3
DH3409	9 ft. (2.7 m)	60 - 130 hp (44.7 - 96.9 kW)	Category 2 and 3



Which Tillage Tool Might Be **Right For You** 

So that's how you do it.

## TipsNotebook.com



**How to Create A Large Vegetable Garden With A One-Bottom Plow**