

Shank Rippers

Eliminate standing water. Rip tree roots along a fence line so your pasture isn't deprived of precious water. Break up tough, compacted soil, giving your garden or crop a chance to really grow.

- Heat-treated steel shanks
- Shank spacing is adjustable (SR1203 only)
- Replaceable wear tips
- iMatch and Quick Hitch compatible (iMatch compatible SR1201 Only)

Model	# of Shanks	Working Depth	Engine HP	Hitch
SR1201	1	14 - 18 in. (35.6 - 45.7 cm)	30 - 75 hp (22.4 - 55.9 kW)	Category 1
SR1202	2	14 - 18 in. (35.6 - 45.7 cm)	60 - 130 hp (44.7 - 96.9 kW)	Category 2
SR1203	3	14 - 18 in. (35.6 - 45.7 cm)	90 - 130 hp (67.1 - 96.9 kW)	Category 2



Cultipackers

Maximize yield with a well-prepared seedbed and great seed-to-soil contact. Great for use by property owners, landscapers, and smaller producers.

- iMatch and/or Quick Hitch compatible
- Heavy duty steel square tube mainframe
- Available in 4, 6, 8, and 12 foot (121.9, 182.9, 243.8, and 365.8 cm) working widths
- 9.5 or 16 inch (24.1 or 40.6 cm) cast iron packer wheels

Model	Row Width	Engine HP	Hitch
CP1148L	48 in. (121.9 cm)	20 - 40 hp (14.9 - 29.8 kW)	Limited Category 1
CP1172L	72 in. (182.9 cm)	20 - 40 hp (14.9 - 29.8 kW)	Limited Category 1
CP1572	72 in. (182.9 cm)	30 - 70 hp (22.4 - 52.2 kW)	Category 1
CP1596	96 in. (243.8 cm)	30 - 125 hp (22.4 - 93.2 kW)	Category 1 and 2
CP1512	144 in. (365.8 cm)	75 - 125 hp (55.9 - 93.2 kW)	Category 2







Plows

Prepare garden space or planting areas with One- and Two-Bottom Plows. Our 3-Point Plows allow you to turn over sod in your field or backyard.

- 14 in. (35.6 cm) or 40 in. (101.6 cm) moldboard width
- Replaceable plow shares, shins, and landslides

Model	Moldboard Width	РТО НР	Hitch
PB1001	One - Bottom / 14 in. (35.6 cm)	25 - 50 hp (13.4 - 37.3 kW)	Category 1
PB1002	Two - Bottom / 40 in. (101.6 cm)	25 - 50 hp (13.4 - 37.3 kW)	Category 1



Middle Buster

Break up hard ground between garden rows with a convenient Middle Buster with a 15×11 in. (38.1 x 27.9 cm) double-wing cutting blade.

- Dig furrows for planting vegetables, digging potatoes or knocking out other small gardening chores
- iMatch compatible

Model	Working Depth	РТО НР	Hitch
PM1001	Up to 12 in. (30.5 cm)	18 - 45 hp (13.4 - 33.6 kW)	Category 1





Subsoiler

This Subsoiler features a .750 x 4 in. (19.0 mm x 10.2 cm) steel shank with reversible point that rips through hard ground to break up compaction, improving water drainage and root growth.

• Standard duty for lower horsepower models

ı	Model	Working Depth	PTO HP	Hitch
	PS1001	Up to 24 in. (61.0 cm)	18 - 45 hp (13.4 - 33.6 kW)	Category 1