

# BRECOflex CO., L.L.C.

High Precision Drive Components

## HT Elastic 4003

	Side 1	Side 2
Carcass	Without special carcass	
Coating	Hytre <sup>®</sup> black T-profile, L-impregnated	Silicone ground
Hardness	40 ± 5 Shore D	30 ± 7 Shore A
Abrasion resistance	High	Very low
Food contact approval	No	FDA
Coefficient of Friction	0.2 ± 0.1μ 0.4 ± 0.1μ	0.4 ± 0.2μ 0.6 ± 0.1μ
Temperature range	-20° up to + 100 ° C	
Anti-static	Yes	
Break strength per cm of width - shaft load*	-	
Elongation per cm of width - shaft load*	10N: 2.5 up to 1.9% 20N: 2.9 up to 3.5% 30N: 4.4 up to 5.2%	
Elasticity - shaft load force per cm of width at 1% elongation*	6.7 ± 2N	
Minimum pulley diameter*	30mm	
Available standard sizes	Length: 710 up to 2200mm Width: 3.0 up to 400mm Thickness: 1.1 up to 2.0mm	
Tolerances	Length: ± 1.0% (min. +/- 2.5mm) Width: ± 0.5mm Thickness: ± 0.1mm	

\* at minimum belt thickness