

208 LOW VOC MULTIPURPOSE CEMENT MEDIUM BODY/AMBER

General Description:

E-Z Weld's 208 Low VOC Multipurpose Cement is a medium bodied, fast set solvent cement. This cement is formulated for joining PVC/uPVC and CPVC pipes and fittings.

Application:

Amber, Medium Body, multi-purpose cement for use on PVC / uPVC and CPVC pipe and fittings up to 6" (150 mm) diameter for Schedule 40 and 4" (100 mm) for Schedule 80. It may be used for pressure applications such as drain, waste, vent, sewer gas, conduit, etc. For superior joint use with E-Z Weld Primer, Purple (No. 212) or Clear (No. 211). Never add thinner or additive. Never use the cement if it is stringy, lumpy or jelly like.

Always follow instructions on the label.

Application temperature: 32°F to 110°F (0°C to 43°C).
Storage temperature: 45°F to 110°F (7°C to 43°C).

Quality Assurance:

Every batch of cement is carefully checked and monitored to assure consistently high quality standards. Records of every batch are kept. All ingredients are purchased from approved suppliers.

Physical Properties:

Color: Amber
Body: Medium Bodied
Set: Fast
Specific Gravity: 0.979
Shelf life: 3 years (Unopened can)

LOW VOC (VOLATILE ORGANIC COMPOUND)

Maximum VOC per SCAQMD 1168/316A: 490 g/l



Availability:

Size	Part No. Regular	(UPC No.)
2 oz	EZ20806	812574012354
1/4pt	EZ20801	892996002324
1/2pt	EZ20802	892996002331
Pt	EZ20803	892996002348
Qt	EZ20804	892996002348
Gal	EZ20805	812574012354

2 oz., ¼ pt., ½ pt., Pt. And Qt. cans are supplied with dauber inside cap. Gallon sizes supplied with plain cap only.

208 LOW VOC MULTIPURPOSE CEMENT MEDIUM BODY/AMBER

Packaging:

Size	2 oz.	¼ Pt	½ Pt	Pt	Qt	Gal
Fluid oz	2	4	8	16	32	128
Liters	0.06	0.12	0.24	0.47	0.95	3.78
Units per case	48	24	24	12	12	6
Weight per case - Lb.	10	9.5	16	15.5	28	54
Weight per case - Kg	4.55	4.32	7.27	7.05	12.73	24.55
Cubic feet per case	0.328	0.260	0.420	0.404	0.762	1.221
Cubic meter per case	0.009	0.007	0.012	0.011	0.022	0.035
Cases per pallet	100	145	90	88	56	27

Safety Precautions:

Ensure adequate ventilation to avoid vapor build up which may cause flash fire. Vapor build up may also cause dizziness, headaches or eye watering. If symptoms are experienced use respiratory protection (NOISH/MSHA TC-23C or equivalent) or leave area and provide more fresh air. Avoid contact with eyes, skin and clothing by use of safety glasses and gloves. Professionals should consult ASTM Standard F402 - 18 Standard Practice for Safe Handling of Solvent Cements, Primers, and Cleaners Used for Joining Thermoplastic Pipe and Fittings. Professional users should also read the Safety Data Sheet for the product.

Inhalation: If breathing is difficult vacate to fresh air. If breathing problems persist seek immediate medical attention.

Eyes: Flush eyes thoroughly with water for 15 minutes. Get immediate medical attention.

Internal: If swallowed give 1 or 2 glasses of water immediately, call physician, hospital or poison control immediately. **DO NOT INDUCE VOMITING.**

Shipping / Transportation:

Material packaged in less than a liter size is exempted under "Limited Quantity Rules" by DOT. These packages may be shipped with the description ORM - D Consumer Commodity. Packages shipped under this description are not subject to shipping paper requirements for flammable materials.

For a liter and larger sizes (gallon and above container):

Proper Shipping Name: Adhesives

Flammable Class: 3

UN No: UN 1133

Packing Group: PG II

REV/12/18