

RC WAX

SACRIFICIAL WAX-BASED ANTI-GRAFFITI COATING

Anti-graffiti



ADVANTAGES OF RC WAX

- ✓ Very resistant to many types of inks and paints
- ✓ Very easy to remove with hot water
- ✓ Perfectly water vapor permeable
- ✓ Not visually perceptible
- ✓ Can be used on all porous graffiti-sensitive surfaces
- ✓ Biodegradable and completely harmless to humans and animals

Description

RC WAX is a biodegradable semi-permanent wax-based anti-graffiti coating for use on surfaces that need protection against graffiti, tags and other contamination. After curing, RC WAX has the property of being very resistant to many types of ink and paint.

The graffiti can be removed very easily with hot water. After the graffiti has been removed, the cleaned areas must be provided with RC WAX again, so that the treated surface is again adequately protected against any subsequent graffiti 'attack' after the curing period.

RC WAX is water vapor permeable and virtually invisible after curing. It is applicable on all porous graffiti-sensitive surfaces such as concrete, brick, natural stone, sand-lime stone, etc. RC WAX can also be used on the most common paint systems.

Substrate

Carefully clean the surface to be treated with a Reynchemie facade cleaner (RC HF CLEANER or RC FACADE P) so that graffiti, loose parts and other contaminations are removed. The substrate must be completely dry and dust-free.

In case of sandblasted surfaces, such as blue limestone, stains can be obtained by poor blasting (= not even). Always place a test area.

Application instructions

Stir or shake RC WAX very well before use. RC WAX should be applied crosswise wet on wet with an interval of ± 2 hours in 2 layers using a low-pressure pump, brush or roller. After applying the first layer, it is allowed to dry for approximately 2 hours (depending on the temperature or humidity). Then a second layer is applied in the same way.

It is recommended to cover windows and frames, although runners and spills can be easily removed with water immediately after use. RC WAX must always be applied undiluted. Always place a test area.

Minimum ambient temperature:	10°C
Maximum relative humidity:	80%
Minimum substrate temperature:	8°C
Maximum substrate temperature:	25°C

Consumption

Consumption depends on the substrate; 6 to 7 m²/liter in a two-layer system.

Security

RC WAX is biodegradable, contains no solvents and is completely harmless to humans and animals.

Remarks

Graffiti can be easily removed with a high-pressure cleaner and hot water. When spraying at pressures of 40 bar and upwards, and a minimum temperature of 70-90°C, RC WAX will melt, removing the graffiti from the surface along with it. After removal, a new layer of RC WAX should be applied.

Cleaning of equipment/spills

With warm water.

Storage / Shelf life

Can be stored for at least 12 months: store in a cool, dry and frost-free place in the original, unopened packaging.

Packaging

5 liters (item no. 120099), 10 liters (item no. 120100) and 25 liters (item no. 120102).

Photos



LP 01-09-2021

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Reynchemie products, are given in good faith based on Reynchemie current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Reynchemie recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Reynchemie reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.