

Technical Data Sheet

VS9003 Black Oscar Ono

[View Product Online](#)



Product Details

Product Code	VS9003
Product Range	Oscar Ono
Construction	Engineered End Grain
Specie	European Oak
Grade	Nature Grade
Process	Brushed & Burnt
Finish	Oiled
Profile	Tongue & Groove
Edge Profile	Bevelled Edge
Top Layer	8mm Solid European Oak End Grain
Core	WBP Birch Plywood

Plank Patterns

Plank A	Grid: 40mm x 1526mm x 20mm - 0.061m ²
Plank B	Brick: 52mm x 1519mm x 20mm - 0.079m ²
Plank C	Arrow: 71mm x 1520mm x 20mm - 0.108m ²
Plank D	Roof Left: 140mm x 1525mm x 20mm - 0.2135m ²
Plank E	Roof Right: 140mm x 1525mm x 20mm - 0.2135m ²
Plank F	Cityscape: 200mm x 1525mm x 20mm - 0.305m ²

Installation Methods

Fully Bonded	Yes (Recommended)
Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes (Please see our underfloor heating guidelines)

Grading Criteria

Known as either natural or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

NB: The product grading criteria is an approximation. Please ask for details.

Technical Criteria

Origin	France	
Responsible certification	FSC Certified	
Formaldehyde emission	EN717-1	E1
Pentachlorophenol emission	CEN/TR 14823	< 5 ppm
Official usage class	NF EN 685	34 (= heavy commercial use)
Emission other dangerous substances		
- Emission COV	ISO 16000	Classe A+
- Emission CMR 1&2		< 1µg/m ³
Reaction to fire	EN13501	Cfl-s1
Characteristics enabling the classification:		
- Average minimum mass volume	EN 14342 : 2013	650 Kg/m ³
- Minimal thickness		20mm (= 12+8mm)
- Conditions of application		glued on subfloor
Thermal resistance	EN 14342	0.092 m ² K/W
Thermal conductivity	EN 14342	λ 0.14 W/m K
Biological durability	EN 335	Risk classification 1

Recommended Installation Accessories

HW650043 Marldon MXA200 Wood Floor Adhesive	Stocked
HW250036 Marldon Rapid DPM 4 Litre	Stocked
HW150097 Strata Acoustic Underlay 3mm	Stocked
VS150090 Strata Acoustic Underlay 5mm	Stocked

Recommended Cleaning Accessories

HW950058 Marldon MXC700 Liquid Wax Care Clear	Stocked
HW950112 Marldon Advanced Cleaning Mop	Stocked
HW950059 Marldon Cleancare 1L	Stocked

MasterSpec

Work Section	6312VS VidaSpace Timber Overlay Flooring System
Link	masterspec.co.nz

Sustainability & Provenance

To back our commitment to sustainable sourcing we have the following independent certification systems to verify they come from sustainably managed forests and sustainable methods are used. The following Certifications apply to a lot of our products, this detail will be found on the first page of our product datasheets. Any queries please get in touch.

Our FSC® and CoC certification gives specifiers, clients and end users assurance of the legality and legitimacy of our FSC timber supply and compliance with government procurement regulations. It demonstrates that we meet the strict tracking requirements for FSC timber products, and that our products come from well-managed forests. The global FSC® certificate database contains information on both Forest Management and Chain of Custody certificates. Our certificate code is SGSHK-COC-510010.

Cradle to Cradle Certified™ is a globally recognized measure of safer, more sustainable products made for the circular economy. Product designers, manufacturers and brands around the world rely on the Cradle to Cradle Certified Product Standard as a transformative pathway for designing and making products with a positive impact on people and planet. Each certification level represents increasingly rigorous achievement across five critical performance categories: Material Health, Material Reutilization, Renewable Energy and Carbon Management, Water Stewardship, and Social Fairness.

E3/AS1 Amendment 7 Information

Timber flooring now needs to be submitted as an Alternative Solution, not an Acceptable Solution for use in kitchens and laundries when a building consent is required. This is a simple process and we are here to support architects and designers with the correct supporting documentation to assist in getting timber floors consented in kitchen and laundry areas.

When installing timber flooring in kitchens, laundries, powder rooms or any space that has sanitary fixtures or sanitary appliances and the build/renovation requires a building consent, to help create an impervious surface, please ensure the following are done:

- Apply a water resistant adhesive such as Marldon D3 PVA (or similar) to all joins of the planks 1.5m out from sanitary fixtures
- Once installation is complete, a flexible waterproof sealant (suitable for wood flooring installations) applied around the perimeter of the floor at least 1.5m out from sanitary fixtures

Note: sanitary fixtures and appliances now include kitchen sinks, dishwashers and washing machines

For further information regarding this refer to www.vidaspace.co.nz/changes-to-e3-as1-acceptable-solutions-timber-in-kitchens/ or get in touch at info@vidaspace.co.nz or 0800 119 388

Installation

We have over 15 floor build up guides so you can select the most fit for purpose installation method of your timber floor. See link to full range of options here www.vidaspace.co.nz/information/flooring-build-up-guides/ Contact one of our timber floor consultants to get assistance on selecting the best installation method. We supply the full range of installation accessories that are shown in the floor build up models. www.vidaspace.co.nz/contact-information/ We recommend all timber floors are installed by an experienced timber floor installer, please see our trusted installers list here www.vidaspace.co.nz/trusted-installer-network/

Care & Maintenance

Protect the future of your investment with the correct cleaning and maintenance regime. Residential and Commercial spaces will require different levels of care & maintenance. See link to our timber floor Care & Maintenance Guides – www.vidaspace.co.nz/information/installation/ Any questions? Get in touch with our timber floor consultants for advice or to reorder products www.vidaspace.co.nz/contact/

Warranty

All VidaSpace products must be installed by a competent installer/contractor who has the necessary skills and experience and can take individual site circumstances into account. VidaSpace warranty will apply only to projects which have been installed, handled and maintained to industry best practice and New Zealand Building Code requirements. It is the responsibility of the specifier to determine the product is suitable and compliant for the application. To view a copy of the full warranty, please contact our team.

Technical Support

Further information and technical support is available by contacting VidaSpace on 0800 119 388.

Special Note: 'In Australia and Europe the same general hierarchy of risk for surface flame spread for finishes is used. While differences exist in the small-scale or intermediate-scale fire test methods adopted in the different jurisdictions, the resulting classifications are considered to be sufficiently similar to the Group Number requirements of NZBC Clause 3.4(a) such that the results can be used directly for the purpose of compliance with Clause C3.4 of the New Zealand Building Code.

Ref: www.building.govt.nz/building-code-compliance/c-protection-from-fire/c-clauses-c1-c6/surface-finishes/

© This technical data sheet was written by VidaSpace Limited, 20 Roe St, Levin, 5571, New Zealand and updated in January 2022. Please ensure that you are using the latest publication by contacting VidaSpace or downloading the latest Technical Data Sheet from the product page on www.vidaspace.co.nz. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.