

Oscar Ono Collection Technical Data Sheet


Inspired by 19th-century cobblestone streets in Paris, Oscar Ono has spent many years reviving the wondrous tradition to give it a new contemporary life. Designed in partnership with Raphael Navot, Oscar Ono is undoubtedly the most luxurious wood flooring collection on the New Zealand market.

- End Grain
- Forêt has 6 Interchangeable Plank Patterns
- Suitable for Underfloor Heating
- Made in Europe.
- Tested for E3/AS1 Requirements

Colours



Natural Forêt



Smoke Forêt



Black Forêt



Natural Opus



Smoke Opus




Black Opus


Individual Product Datasheets are available for download on our website.

Forêt Plank Patterns


Plank A - Grid




Plank B - Brick




Plank C - Arrow



Plank D - Roof Left



Plank E - Roof Right



Plank F - Cityscape



Grading Criteria



Nature Grade

Known as either nature or rustic grade this allows a virtually limitless size and number of knots. Heartwood will be used, there will be colour variation, sapwood and filler; you should expect checks (cracks across the growth ring) and possibly some end shake (cracks between the rings). The colour of the filler is carefully selected to compliment the wood rather than to match it exactly and it may vary from batch to batch.

NB: The product grading criteria is an approximation. Please ask for details.

Installation Methods

Glue Down	Yes
Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes (Please see our underfloor heating guidelines)
Wet Areas	Suitable in Kitchens, Laundries, & Toilet Rooms
Suitable Applications	Flooring, Walls & Ceilings

Recommended Installation Accessories

VidaSpace Wood Floor Adhesive	Stocked
HW250036 Marldon Rapid DPM 4 Litre	Stocked
HW150097 Strata Acoustic Underlay 3mm	Stocked
HW150090 Strata Acoustic Underlay 5mm	Stocked

Recommended Cleaning Accessories

HW950112 Marldon Advanced Cleaning Mop	Stocked
HW950059 Marldon Cleancare	Stocked
HW950058 Marldon Liquidwax Care Clear	Stocked

MasterSpec



Work Section
Link

6312VS VidaSpace Timber Overlay Flooring System
masterspec.co.nz

Product Details

Board	Construction	Engineered End Grain
	Species	European Oak
	Pattern	6 Interchangeable Planks
	Backing	WBP Birch Plywood
	Thickness	20mm
	Wear Layer	8mm
	Click System	Tongue & Groove

Dimensions	Forêt Plank A: Grid	40mm x 1526mm x 20mm - 0.061m2
	Forêt Plank B: Brick	52mm x 1519mm x 20mm - 0.079m2
	Forêt Plank C: Arrow	71mm x 1520mm x 20mm - 0.108m2
	Forêt Plank D: Roof Left	140mm x 1525mm x 20mm - 0.2135m2
	Forêt Plank E: Roof Right	140mm x 1525mm x 20mm - 0.2135m2
	Forêt Plank F: Cityscape	200mm x 1525mm x 20mm - 0.305m2
	Opus Panel	490mm x 470mm x 20mm - 0.2303m2

Finish	Edge Profile	Bevelled Edge
	Finish	UV Oiled
	Structure	Brushed

Warranty	Residential	10 Years
	Commercial	10 Years


Technical Data	Origin		France
	Responsible certifications		FSC® certified FSC C129187
	Janka Hardness Rating		1,120 lbf (4,890N)
	Underfloor heating		ok
	Thermal Resistance	EN 14342	0.092 m2K/W
	Thermal Conductivity	EN 14342	0.14 W/m K
	Recycling		ok
	Formaldehyde emission	EN717-1	Class E1 (<0.13 ppm)
	PCP Emissions (pentachlorophenol	CEN/TR 14823	< 5 ppm (PCP free)
	Official usage class	NF EN 685	34 (= heavy commercial use)
	Emission other dangerous substances - Emission COV	ISO 16000	Classe A+
	Emission other dangerous substances - Emission CMR 1&2		< 1µg/m3
	Characteristics enabling the classification		
	- Average minimum mass volume	EN 14342 : 2013	650 Kg/m3
	- Minimal thickness		20mm (= 12+8mm)
	- Conditions of application		glued on subfloor
	Biological durability	EN 335	Risk classification 1
	European reaction to fire classification	EN 13501	Cfl-s1
	Reaction to fire - Walls & Ceilings		Group 3 - To achieve Group 1-s fire rating apply Zone 92 intumescent coating or similar.

Product Codes	Natural Forêt	Nature Grade	VS9001
	Smoke Forêt	Nature Grade	VS9002
	Black Forêt	Nature Grade	VS9003
	Natural Opus	Nature Grade	VS9005
	Smoke Opus	Nature Grade	VS9006
	Black Opus	Nature Grade	VS9007

Floor Build-up System Guides

Combining high performance products with low environmental impact and delivering quality without compromise, our products overcome build challenges, saving time and speeding up your build. Simply make your selection from the options below and you'll receive full details of the complete sub-floor build-up you need to support your project.

Timber or Chipboard Subfloor Systems



VS103 Gluing timber floor over a timber subfloor


[Download](#)



VS104 Gluing timber floor over a timber subfloor with Strata underlay


[Download](#)

Concrete Subfloor Systems




VS203 Gluing timber floor over concrete subfloor with underfloor heating

[Download](#)




VS204 Gluing Mosaic/Herringbone timber floor over concrete subfloor

[Download](#)



VS206 Gluing timber floor over concrete subfloor with underfloor heating

[Download](#)




VS207 Gluing timber floor over a concrete subfloor using Strata underlay

[Download](#)




VS208 Gluing timber floor over a concrete subfloor using MXS120 Primer

[Download](#)




VS209 Gluing timber floor over damp concrete subfloor using DPM

[Download](#)



VS210 Gluing timber floor over concrete subfloor with underfloor heating

[Download](#)



VS211 Gluing timber floor over concrete subfloor using DPM & Strata

[Download](#)

Sustainability & Provenance

To back our commitment to sustainable sourcing we have the following independent certification systems to verify they come from sustainably managed forests and sustainable methods are used. The following Certifications apply to a lot of our products, this detail will be found on the first page of our product datasheets. Any queries please get in touch.

Our FSC® and CoC certification gives specifiers, clients and end users assurance of the legality and legitimacy of our FSC timber supply and compliance with government procurement regulations. It demonstrates that we meet the strict tracking requirements for FSC timber products, and that our products come from well-managed forests. The global FSC® certificate database contains information on both Forest Management and Chain of Custody certificates. Our certificate code is SGSHK-COC-510010. Parky is FSC Certified on request.

E3/AS1 Amendment 7 Information

Timber flooring now needs to be submitted as an Alternative Solution, not an Acceptable Solution for use in kitchens and laundries when a building consent is required. This is a simple process and we are here to support architects and designers with the correct supporting documentation to assist in getting timber floors consented in kitchen and laundry areas.

When installing timber flooring in kitchens, laundries, powder rooms or any space that has sanitary fixtures or sanitary appliances and the build/renovation requires a building consent, to help create an impervious surface, please ensure the following are done:

- Apply a water resistant adhesive such as Marldon D3 PVA (or similar) to all joins of the planks 1.5m out from sanitary fixtures
- Once installation is complete, a flexible waterproof sealant (suitable for wood flooring installations) applied around the perimeter of the floor at least 1.5m out from sanitary fixtures

Note: sanitary fixtures and appliances now include kitchen sinks, dishwashers and washing machines

For further information regarding this refer to www.vidaspace.co.nz/changes-to-e3-as1-acceptable-solutions-timber-in-kitchens/ or get in touch at info@vidaspace.co.nz or 0800 119 388

Installation

We have over 15 floor build up guides so you can select the most fit for purpose installation method of your timber floor. See link to full range of options here www.vidaspace.co.nz/information/flooring-build-up-guides/. Contact one of our timber floor consultants to get assistance on selecting the best installation method. We supply the full range of installation accessories that are shown in the floor build up models. www.vidaspace.co.nz/contact-information/. We recommend all timber floors are installed by an experienced timber floor installer, please see our trusted installers list here www.vidaspace.co.nz/trusted-installer-network/.

Care & Maintenance

Protect the future of your investment with the correct cleaning and maintenance regime. Residential and Commercial spaces will require different levels of care & maintenance. See link to our timber floor Care & Maintenance Guides – <https://www.vidaspace.co.nz/downloads-resources#Care-Maintenance>. Any questions? Get in touch with our timber consultants for advice – www.vidaspace.co.nz/contact/.

Warranty

All VidaSpace products must be installed by a competent installer/contractor who has the necessary skills and experience and can take individual site circumstances into account. VidaSpace warranty will apply only to projects which have been installed, handled and maintained to industry best practice and New Zealand Building Code requirements. It is the responsibility of the specifier to determine the product is suitable and compliant for the application. To view a copy of the full warranty, please contact our team. Download Online

Technical Support

Further information and technical support is available by contacting VidaSpace on 0800 119 388.

© This technical data sheet was written by VidaSpace Limited, 20 Roe St, Levin, 5571, New Zealand and updated in July 2023. Please ensure that you are using the latest publication by contacting VidaSpace or downloading the latest Technical Data Sheet from the product page on www.vidaspace.co.nz. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

01-July-2023/NZ