



Producing dialogue with exceptional precision, this speaker was specifically designed to be used in home theatre systems. With its subtle design, the Sonix Mk3 blends into its surroundings.

High frequencies are delivered by a 26mm ring radiator tweeter, with central waveguide for improved intelligibility and transparency. Bass and midrange are delivered by dual 100mm drivers, with dual front ports releasing bass energy forward – making it ideal for placing inside your TV cabinet.

Perfectly sized for placement around AV components, the Sonix Mk3 is designed to slip neatly into most TV cabinets and joinery, allowing your screen to be the hero.

For the ultimate sound experience at home, play it through Krix.



FEATURES

- Compact size fits most TV cabinets
- Bring movie dialogue to life
- No more need for TV speakers



	Sonix Mk3
Frequency Range	65Hz - 40kHz (in room response)
Power Handling	20 - 140 Watts RMS recommended amplifier power
Sensitivity	88dB (2.83V / 1m)
Impedance	Nominal 6 Ohms (Minimum 4.2 Ohms)
Configuration	D'Appolito, 2-way
Low Frequency Driver	2 x nominal 100mm (4") doped paper cones. 26mm (1") voice coil wound on high powered aluminium former
High Frequency Driver	26mm (1") dual concentric diaphragm with wave-guide, centre plug for controlled directivity
Enclosure Type	Bass reflex, front vented with internal X bracing
Vent Location	Front
Dimensions	125mm high x 435mm wide x 160mm deep
Net Weight	4kg

FINISHES



Black Woodgrain



krix.com

Sonix Mk3 Specifications Sheet-001