

Home theatre on a grand scale: this centre channel speaker produces exceptional vocal intelligibility and is designed to truly match the pace of our high energy Neuphonix Mk2 floorstanding speakers.

Multiple 130mm bass drivers deliver punchy, ground-shaking bass energy. A 130mm midrange driver and 26mm tweeter complete the picture, reproducing vocals and sound effects with meticulous precision and depth that will defy the dimensions of your room.

The fully mitred construction combined with extra bracing results in a very strong and resonant free enclosure. Other updates include a brushed aluminum terminal plate with gold plated brass binding posts and a stylish scalloped edge grille.

The Epicentrix Mk2, like the Neuphonix Mk2 has dual terminals for biwiring or bi-amping.

Bring dialogue and special effects to life. Put yourself at the epicentre of the action.


## FEATURES

- Exceptional vocal intelligibility
- Ultimate power and precision
- Refined styling
- Brushed aluminium terminal plate




	Epicentrix MK2
Frequency Range	35Hz - 40kHz (in room response)
Power Handling	50 - 300 Watts RMS recommended amplifier power
Sensitivity	90dB (2.83V / 1m)
Impedance	Nominal 6 Ohms (Minimum 4.3 Ohms)
Configuration	3-way
Low Frequency Driver	4 x nominal 130mm (5") coated paper cones. 26mm (1"), voice coil wound on high powered aluminium former
Mid Range Driver	1 x nominal 130mm (5") coated paper cone. 26mm (1"), voice coil. Copper shorting ring and oversized magnets
High Frequency Driver	26mm (1") dual concentric diaphragm with wave-guide, centre plug for controlled directivity
Enclosure Type	Dual bass reflex chamber, sealed midrange chamber
Vent Location	Front
Dimensions	233mm high x 910mm wide x 355mm deep
Net Weight	24kg


## FINISHES



Black Ash



Atlantic Jarrah



Blackwood



**krix.com**

Epicentrix Mk2 Specifications Sheet-004

ADELAIDE | 14 Chapman Road, Hackham, SA, 5163, Australia

T +61 8 8384 3433

F +61 8 8384 3419

listen@krix.com.au

Pg. 2 of 2