1850 SUPERCAB









1850 SUPERCA



SAFETY FEATURES:

NZ CPC Boat Safety Standards
USCG Boat Safety Standards
LED Nav Lights
Reserve Buoyancy
ABP Safety Standards

SPECIFICATIONS:

of Lon toArtono.	
Length Feet (Metres)	18.5'ft (5.6m)
Max Adults	6
Recommended HP	115hp
Maximum HP	140hp
Maximum Engine Weight	220kg (485lbs)
Leg Length	25"
Fuel Tank	120L (32gal)
External Beam	2.24m (88")
Internal Beam	1.65m (65")
Deadrise	17°
Tube Thickness	3mm (1/8")
Hull Thickness	4mm (5/32")
Sealed Buoyancy Capacity (App	rox) 1570L (415gal)
Dry Hull Weight (Approx)	740kg (1631lbs)
Tow Weight (Approx)	1250kg (2756lbs)
Length on Trailer	6.70m (22ft)



STANDARD FEATURES:

Arrow Pontoons
Game Chaser Transom
Bow storage shelves
SARCA aluminium fairlead
Foot rest & cargo barrier
Battery and oil tank storage
Bilge pump and well
Graphics package
Rear fold-down seats

STANDARD FEATURES:

•		
Rodholders in	n aft coamings	
Stabi cleats		
Steering - No	n-feedback	
Central batte	ery box	
Wingstyle co	amings	
Cantilever se	eat bases with storage	
Skipper seats	s with swivels	
Maxwell RC6	capstan	
Stabicraft Mu	ultiholders (drink and tackle holders)	

OPTIONAL FEATURES:

Rear boarding ladder 2-step Large So-Pac hatch (fitted in central transom box opening) Central mounted windscreen wiper Removable filleting/baitboard





E: enquiries@stabicraft.com P: 0064 3 211 1828

A: 345 Bluff Highway, Invercargill, New Zealand

