





1550 FISHER

SAFETY FEATURES:

Reserve Buoyancy
NZ CPC boat safety standards
US Coastguard boat safety standards
LED navigation lights
Australian Builders Plate boat safety standards

SPECIFICATIONS:

	Length Feet (Metres)	15.5ft (4.72m)
	Max Adults	5
	Recommended HP	50
	Maximum HP	75
	Maximum Engine Weight	166kg (366lbs) Yamaha F75
	Leg Length	20"
	External Beam	2.02m (79.5")
	Internal Beam	1.46m (57.5")
	Deadrise	15°
	Tube Thickness	2.5mm (3/32")
	Hull Thickness	4.0mm (5/32")
	Sealed Buoyancy Capac	ity (Approx) 984L (260gal)
	Dry Hull Weight (Approx)	415kg (915lbs)
	Tow Weight (Approx)	740kg (1631lbs)
	Length on Trailer	6.00m (19'9")



STANDARD FEATURES:

Bow storage shelves Foot rest & cargo barrier Battery and oil tank storage Bilge pump and well Cantilever seat bases with storage Graphics package Rodholders in aft coamings Skipper seats upholstered Stabi cleats Stabicraft Multiholders (drink and tackle holders) Steering - Planetary Wingstyle coamings Alloy towing eye with S/S wear sleeves Anchor rope and chain storage locker Battery isolation switch Shimano tackle boxes

STANDARD FEATURES:

Soft touch Gussi steering wheel
4-way dash switch panel
Arrow Pontoons
XOS walk-through windscreen
Single axle trailer
70L Icey-Tek Chilly bin with split lid + squab
Folding seat behind starboard cantilever + squab
Roller Trailer
60L fuel tank (standard Australia only)

OPTIONS:

Anchor, chain and warp
Adhesive fendering
External gunwale handrails
Injected foam in pontoons
Live bait tank

OPTIONS:

Paint - Cabin only
Paint - Belting up
Paint - External Pontoon
Paint - Metallic upgrade
Rear boarding ladder (T-bar 2 step)
Rod and canopy arch
Tube floor matting
Washdown pump kit
Keel wear strip
Maxwell anchor max winch
60L fuel tank (optional NZ only)



E: enquiries@stabicraft.com P: 0064 3 211 1828

A: 345 Bluff Highway, Invercargill, New Zealand

www.stabicraft.com

