

Section 1: Identification of the substance/mixture and of the company/undertaking

Product form: Liquid

Substance name:

Black Elixir Rapid Dry Additive by GuardTop®

Synonyms: Asphalt Sealer Rapid Dry Additive

Manufacturer

GuardTop LLC 30012 Ivy Glenn Dr., Suite 145 Laguna Niguel, CA 92677 (949) 218-4319

Emergency telephone number

CHEMTREC (800) 424-9300

Section 2: Hazards identification

Classification of the substance or mixture:Eye IrritantCategory 2ASkin Corrosion/IrritationCategory 3



Signal Word: WARNING

Hazard Statements

- May be harmful if swallowed.
- May cause mild skin irritation.
- Will cause eye irritation in the event of eye exposure.

Precautionary Statements

- Obtain and read instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Exposure to hot material may cause thermal burns.

Issued: May 26th, 2022



Section 3: Composition/information on ingredients

Chemical NameAmountCAS NumberAcrylic Polymer<45.00%</td>NA MixtureAsphalt Residual<10.00%</td>08052-42-4Methanol<2.0%</td>67-56-1Carbon Black<5.0%</td>1333-86-4

Section 4: First aid measures

First-aid measures general: Remove from contaminated area.

First-aid measures after inhalation: If breathing is difficult, remove to fresh air, give oxygen. Get immediate

medical attention.

First-aid measures after skin contact: Wash skin with soap and water. Wear protective glove to minimize skin

contamination.

First-aid measures after eye contact: Hold eyelids apart and flush eyes with plenty of water for at least 15

minutes. Get medical attention if irritation develops or persists. Burns due to contact with heated material require immediate medical attention.

First-aid measures after ingestion: If conscious, give two glasses of water or milk. Get immediate medical

attention. Do not induce vomiting due to danger of aspirating liquid into

lungs. Gastric lavage may be required.

Most important symptoms and effects, both acute and delayed

Eyes:IrritationSkin:IrritationInhalation:Irritation

Chronic Effects: No known hazards in normal industrial use.

Section 5: Firefighting measures

Extinguishing media

Suitable extinguishing media: Dry chemical, carbon dioxide, water spray or foam.

Unsuitable extinguishing media: Exercise care when using water as contact with hot asphalt products may

produce steam and violent foaming.

Special hazards arising from the substance or mixture

Fire hazard: Product is an aqueous solution. Heated product may produce hazardous

fumes, decomposition products or residues. Small quantities of hydrogen

sulfide may be released upon heating.

Explosion hazard: None

Reactivity: Avoid contact with strong bases.

Issued: May 26th, 2022



Advice for firefighters

Firefighting instructions: Decomposition may produce fumes, smoke, oxides of carbon and

hydrocarbons and possible small quantities of hydrogen sulfide. Avoid breathing vapors from heated material. Combustion may produce CO,

NOx, Sox and reactive hydrocarbons.

Protection during firefighting: As in any fire, wear self-contained breathing apparatus pressure-demand

MSHA/NIOSH approved and full protective gear.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures: Clean up spills immediately using appropriate personal protective

equipment.

For non-emergency personnel

Protective equipment: Gloves, safety with side shields, boots.

Emergency procedures: Absorb spills with absorbent material. Contain spilled liquid with sand or

earth.

For emergency responders

Protective equipment: Gloves, safety glasses with side shields, boots.

Emergency procedures: Stop the source of the leak or release. Clean up releases as soon as

possible.

Environmental precautions

Prevent contamination of soil, surface water or groundwater.

Methods for containment/clean up

Absorb spills with inert material and place into separate waste container. Contain spilled liquid with sand or earth. Contain liquid to prevent contamination of soil, surface water or groundwater. Large spillage should be dammed-off and pumped into containers.

Section 7: Handling and storage

Precautions for safe handling

Use only as directed in well ventilated area. Avoid prolonged contact with skin. Avoid contact with eyes. Avoid breathing mist or vapors. Do not eat, smoke, or drink with contaminated hands. Do not discard into sewers or drains. Always wear personal protective equipment.

Storage conditions: Keep all containers tightly sealed. Do not store in direct sunlight. Store at

room temperature.

Issued: May 26th, 2022



Section 8: Exposure controls/personal protection

Engineering Controls: Facilities storing or utilizing this material should be equipped with an

eyewash facility and a safety shower.

Eye/Face Protection Requirements: Where contact with this material is likely, eye protection is recommended.

Skin Protection Requirements: Selection of specific items such as gloves, boots, apron or full-body suit will

depend on operation and potential exposure.

Respiratory Protection Requirements: Where there is potential for airborne exposure in excess of applicable

limits, wear NIOSH/MSHA approved respiratory protection.

Exposure Guidelines:

MethanolOSHA PEL200 mg/M3Asphalt ResidualOSHA PEL5 mg/M3Carbon BlackOSHA PEL3.5 mg/M3

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid

Appearance: Brown to Black

Odor: Asphalt Odor

pH: 7-8

Freezing point:32 degrees FSpecific Gravity:1.4-1.7 (Water=1)Boiling point:212 degrees F

 Flash point:
 None

 UEL:
 N/A

 LEL:
 N/A

Vapor pressure: Same as water mm Hg @ 21 degrees C

Solubility:Soluble in waterDecomposition temperature:275 degrees F

Viscosity: 78 KU's

Issued: May 26th, 2022

Page 4 of 6



Section 10: Stability and reactivity

Reactivity: Low

Chemical stability: This compound is stable at ambient conditions.

Possibility of hazardous reactions: Low

Conditions to avoid: Avoid extreme temperatures. **Incompatible materials:** Avoid contact with strong bases.

Hazardous decomposition product: Decomposition will not occur if handled and stored properly.

Polymerization: Hazardous polymerization will not occur.

Section 11: Toxicological information

None Tested

Section 12: Ecological information

Environmental Hazards

Contaminated Materials:

This product is considered to be biodegradable. There is no evidence to show that this product will cause adverse ecological effects on the environment.

Section 13: Disposal considerations

Waste Disposal: This product, as supplied, when discarded or disposed of, may be a

hazardous waste according to Federal regulations (40 CFR 261). Under the Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user of the product to determine whether the material is a hazardous waste subject to RCRA. Treat or dispose of waste material in accordance with all local, state/provincial and national requirements. Avoid disposal

into wastewater treatment facilities. Treat as product waste.

Container Disposal: Unclean empty containers should be disposed of in the same manner as the

contents.

Section 14: Transport information

Product Label: Asphalt Sealer Rapid Dry Additive
UN Number: Non-hazardous, no UN number

DOT Shipping Name: Non Regulated, Water Based Asphalt Emulsion

DOT Hazard Class: Non-Hazardous

Section 15: Regulatory information

None

Issued: May 26th, 2022



Section 16: Other information

Special Hazard:

Indication of changes 1 NFPA health hazard: 0 NFPA fire hazard: 0 NFPA reactivity: 1 **Personal Protection Index: HMIS III Rating** Health: 1 0 Flammability: 0 Reactivity:

IMPORTANT: The information presented herein, while not guaranteed, is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and GuardTop LLC. assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer.

None

Issued: May 26th, 2022