

DESCRIPTION

- Slim profile wall/ flood mounted family is available with remote controlled 5-Step changeable CCT for 15W and 28W models
- Die-cast aluminum housing with UV stabilized clear polycarbonate lens
- Chip and fade resistant powder coat finish
- Reliability tested LED chips and driver assure long life
- 120V
- Button-type photocell in 45W and 75W for dusk-to-dawn operation
- Easy installation with wall mount back plate (can be removed for mounting on ground J-box)
- Multiple beam directions via tool-less pivot
- ETL Listed for Wet Locations, IP65



FSNX15



FSNX28




FSNX50



FSNX80

SPECS AT A GLANCE

Model	FSNX15	FSNX28	FSNX50	FSNX80
Nominal Wattage	15W	28W	45W	75W
CCT (K)	2700K-5000K (Changeable)		4000K	
Lumens (LM)	1650	3000	5301	8139
Efficacy (LPW)	110	107	118	109
CRI	>70			
Input Voltage	120V			
Operating Temp.	-30°C to +40°C (-22°F to +104°F)			
Certifications	ETL, IP65			



	FSNX15	FSNX28	FSNX50	FSNX80
A	7.7" (196 mm)	8.7" (221 mm)	10" (251 mm)	11.1" (283 mm)
B	4.4" (111 mm)	4.8" (121 mm)	5.7" (146 mm)	6.3" (161 mm)
C	4.7" (120 mm)	4.7" (120 mm)	4.7" (120 mm)	4.7" (120 mm)
D	5.4" (136 mm)	5.4" (136 mm)	5.4" (136 mm)	5.4" (136 mm)
Weight	1.5 lbs	1.8 lbs	2.4 lbs	3.7 lbs

ORDERING INFORMATION

Catalog Number	Description
FSNX15-5CCT-BZ	Flood Light, 15W LED, 2700-5000K CCT, 1650 lm, 120V, 110 LPW, 70 CRI, Bronze
FSNX28-5CCT-BZ	Flood Light, 28W LED, 2700-5000K CCT, 3000 lm, 120V, 107 LPW, 70 CRI, Bronze
FSNX50-PC-4K-BZ	Flood Light, 45W LED, 4000K CCT, 5301 lm, 120V, 118 LPW, 70 CRI, Photocell, Bronze
FSNX80-PC-4K-BZ	Flood Light, 75W LED, 4000K CCT, 8139 lm, 119V, 109 LPW, 70 CRI, Photocell, Bronze