



CEC DOE FC

PERFORMANCE FEATURES

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Letters 6" height with 3/4" stroke. Optional RED or GREEN letters.
- SALIDA faceplate available.
- Single or double face (Universal)
- Universal J-box mounting pattern.
- 120V/277VAC Dual voltage operation.
- Ultra bright RED or GREEN LED's
- Built-in 1.2V 1000mAh Nickel cadmium battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full charge time.
- Test switch and charge indicators.
- Test switch and charge indicators.
- 0° to 40° C Indoor damp location listed.
- Five years warranty for the electrical parts and housing.

ORDERING INFORMATION

Model Section		ES-C-S		
FAMILY	LENS	HOUSING COLOR	TYPE	LETTER
ES-C-S	R-RED	Blank White	E (Battery Backup)	BLANK(EXIT)

ELECTRICAL INFORMATION

Model	Rated Voltage	Input Current	Input Watt	LED Type	Charging Time	EMERGENCY RUN TIME
ES-C-S	120/277V	0.015/0.008A	1.9W	12Pcs Red LEDs	24 Hrs	90 Mins

PACKING INFORMATION

SKU #	Standard Pack	Dimension	Master Pack	Dimension
ES-C-S	1 Pack	11.61X7.48X1.73 in	6 Pack	15.35X13.19X9.06 in

PRODUCT DIMENSIONS

