



LED Troffer Retrofit Kit

DATE: _____ LOCATION: _____
 TYPE: _____ PROJECT: _____
 CONSTRUCTION: _____



PERFORMANCE FEATURES

UL Listing

Suitable for damp locations

Lifespan:

Lumen Maintenance, L70 > 54,000 hours
 Rated Life: 100,000 hours

Optional Accessories

- Surface mount kit | Drywall mount kit
- Suspension mount kit
- Occupancy sensor
- EM battery

LEDs:

Long-life, high-efficacy, micro-power LEDs

Finish

Long lasting white finish with high durability

Flicker:

Produces no greater than 30 percent flicker at 200 Hz or below when paired with control devices per CEC Title 24 JA10

Housing and lens

Cold-rolled steel, Frosted PMMA lens

Mounting

- Grid ceiling • Recessed drywall
- Surface mounting • Suspended installation

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. The dim-to-off voltage threshold of optional 12V AUX integrated driver ranges from 0.1V to 0.5V.


SKU GUIDE

Model Section		RTR04-45W-CCT-DV2-F-WHSM						
RTR0		45W	CCT	DV2		F	WHSM	
BODY TYPE PREFIX	MODEL NAME	WATTAGE	CCT (if selectable = CCT)	DRIVER	VOLTAGE	ELECTRICAL OPTIC/LENS	HOUSING FINISH	MOUNTING
RTR0	2 - 2X2 FT 4 - 2X4 FT	40W - 40/35/30 45W - 45/38/34	CCT - 3500K/ 4000K/5000K (3-Way CCT Selectable)	D - 0-10V Dimming	V2 - 120-277V (Universal Voltage)	F-Frosted Lens	WH-White Finish	SM-Surface Mount

SKU SPECIFICATION

SKU #	Nominal Wattage	CCT	Lumens	Efficacy (LPW)	CRI	Input Voltage	Operating Temp.	Certifications	Avail Options
RTR02-40W-CCT-DV2-NA-F-WHSM	40/35/30	3500K/ 4000K/ 5000K	5000/ 4375/ 3750	125	>80	120-277V	-4(Degree) F/ -20(Degree)C to 122(Degree) F/ -50(Degree) C	UL listed DLC listed	Occupancy sensor, EM battery
RTR04-45W-CCT-DV2-NA-F-WHSM	45/38/34	3500K/ 4000K/ 5000K	5625/ 4750/ 4250	125	>80	120-277V	-4(Degree) F/ -20(Degree)C to 122(Degree) F/ -50(Degree) C	UL listed DLC listed	Occupancy sensor, EM battery


PRODUCT DIMENSIONS



PACKAGING DIMENSIONS

SKU #	Standard Pack	Dimension
RTRO2-40W-CCT-DV2-NA-F-WHSM-2	2 Pack	L 22.7 in x W 22.7in x H 10.1in
RTRO4-45W-CCT-DV2-NA-F-WHSM	2 Pack	L 49.7 in x W 24.7in x H 10.3in

PHOTOMETRICS



Maximum Candela = 1953.6 Located At Horizontal Angle = 112.5, Vertical Angle = 5
 # 1 - Vertical Plane Through Horizontal Angles (112.5 - 292.5) (Through Max. Cd.)
 # 2 - Horizontal Cone Through Vertical Angle (5) (Through Max. Cd.)

Medinah Power

Contact us: For support & assistance, please feel free to contact us below.

E-Mail: info@medinahpower.com | Web: www.medinahpower.com | Ph: +1 (844) 870-5337

