

CHARACTERISTICS

- Telescopic tube set
- Available in 2 versions
 - \cdot For pool width between 3,3 4,5m
 - \cdot For pool width between 4,3 5,5m
- Made of glass fibre reinforced vinyl ester
- Compact and lightweight
- Robust design

ADVANTAGES

- Easy to transport, maximum length 2,155m
- Available from stock
- Compatible with salt electrolysis
- Smooth and easy installation
 - · ONE man installation
 - · During pool construction



TECHNICAL SPECIFICATIONS

CHARACTERISTICS	UNIT	DCTS-450	DCTS-550
Range length	mm	3300 - 4500	4300 - 5500
Outside diameter	mm	159	159
Outer tube quantity	рс	2	2
Outer tube length	mm	1500	2000
Inner tube quantity	рс	1	1
Inner tube length	mm	2000	2000
Shipping dimensions (L*W*H)	mm	2055*335*185	2155*335*185
Shipping weight	kg	30	36
Warranty	year	3	3

TO COMBINE WITH

MOTOR	MOUNTING SYSTEM	CONTROL UNIT
COVER Motor p. 74	COVER Wall Duct p. 76	LINK Cover p. 92
	COVER Cable Duct p. 78	LINK Master p. 94
	COVER Hanging System p. 80	