

Proline

Sheet Steel Enclosed Switchfuses

Our Proline range is designed to offer cost effective, quality solutions for most indoor applications.

- AC22A Rated 415V Phase-To-Phase, 240V Phase-To-Neutral
- BSEN 60947-3 conformity
- Door interlocked padlockable handles on hinged units
- Alternative pole configurations and auxiliary contacts available
- Removable gland plate top & bottom (knock-outs on SPN units)
- Ingress protection IP41



Nominal Rating I _e 415V	Ordering Reference TP&N	Ordering Reference 4P	Fuse (included)	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
				H	W	D	A	Ø	B
Switchfuses with hinged door									
20A	SF20	SF20-4P	10x38	300	180	110	10 cage		70
32A	SF32	SF32-4P	10x38	300	180	110	16 cage		70
63A	SF63	SF63-4P	A3	395	230	110	20	M8	105
100A	SF100	SF100-4P	A3	395	230	110	20	M8	105
125A	SF125	SF125-4P	A3	395	230	110	20	M8	105



SP&N Switchfuses with screw lid									
63A	SF63SPN		22x58	250	115	60	25 cage		80
80A	SF80SPN		22x58	250	115	60	25 cage		80
100A	SF100SPN		22x58	305	135	60	25 cage		110



SP&N Switchfuses with screw lid and 3rd amendment flap									
63A	SF63SPN-3A		22x58	250	115	90	25 cage		80
80A	SF80SPN-3A		22x58	250	115	90	25 cage		80
100A	SF100SPN-3A		22x58	305	135	90	25 cage		110

Proline Sheet Steel Enclosed Isolators

Nominal Rating I _e 415V	Ordering Reference TP&N	Ordering Reference 4P	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
			H	W	D	A	Ø	B
Load Break Isolators with hinged door								
20A	LB20	LB20-4P	300	180	110	10 cage		130
32A	LB32	LB32-4P	300	180	110	16 cage		130
63A	LB63	LB63-4P	300	180	110	25 cage		130
100A	LB100	LB100-4P	395	230	110	20	M8	145
125A	LB125	LB125-4P	395	230	110	20	M8	145
160A	LB160	LB160-4P	395	230	110	20	M8	145




The fireman switch is a switch disconnecter/isolator for special applications. You can often see these switches on the outside wall of commercial buildings. They are designed to be easy to identify and are operated by a fireman's hook to turn off neon-lighting or other hazardous electrical equipment in the event of a fire.

- Die cast aluminium enclosure
- Operates with fireman hook or axe - down for OFF
- Two handed switch ON
- 2 pole 240V AC22A
- 2 x M25 gland entries top and bottom



Nominal Rating I _e 240V	Ordering Reference	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
		H	W	D	A	Ø	B
Fireman Switch							
25A	FMS25/2	130	109	60	10 cage		50



The Proline range is not customisable. See pages 04-05 for options that can feature bespoke requirements including:

- Spreader terminals
- Auxiliary contacts
- Larger enclosures for additional cable room
- GRP, Stainless, Rain hoods and IP65 etc.

