

Sheet Steel Enclosed Double Break Switchfuses

- Fully load rated AC23A 415-690V
- BSEN 60947-3 conformity
- Door interlocked padlockable handle
- IP2X terminal shrouds
- Removable gland plate top (up to 700 H) and bottom
- Fitted with general purpose BS88 HRC fuses
- Double break, fuses isolated on both sides
- Ingress protection IP55



Nominal Rating I _e 415V		Ordering Reference TP&N	Ordering Reference 4P	BS88 Fuse (included)	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
					H	W	D	A	Ø	B
63A	30kW	ST IHF 6/3+N+F	ST IHF 6/4+F	A3	400	300	200	14	M6	149
100A	45kW	ST IHF 10/3+N+F	ST IHF 10/4+F	A4	500	400	200	20	M8	179
125A	55kW	ST IHF 12/3+N+F	ST IHF 12/4+F	B2	500	400	200	20	M8	194
160A	75kW	ST INF 16/3+N+F	ST INF 16/4+F	B2	500	400	200	20	M8	194
200A	105kW	ST INF 20/3+N+F	ST INF 20/4+F	B2	700	500	250	25	M10	294
250A	132kW	ST INF 25/3+N+F	ST INF 25/4+F	B3/B4	700	500	250	30	M10	282
315A	155kW	ST INF 30/3+N+F	ST INF 30/4+F	B3/B4	700	500	250	30	M10	282
400A	200kW	ST INF 40/3+N+F	ST INF 40/4+F	B3/B4	800	600	300	40	M12	332
500A	355kW	ST INF 50/3+N+F	ST INF 50/4+F	C2	1000	600	300	40	M12	400
630A	355kW	ST INF 63/3+N+F	ST INF 63/4+F	C2	1000	600	300	40	M12	400
800A	400kW	ST INF 80/3+N+F	ST INF 80/4+F	C3	1200	800	300	40	M12	500



GRP enclosures are available in a variety of sizes



Units can be fitted in floor standing enclosures for additional wiring room