

Sheet Steel Enclosed 4 Pole Contactors

- 110V - 240V coil with fuse protection
- Normally open contactors
- IEC 60947-4-1 rated
- IP2X terminal shrouds
- Ingress protection IP55



AC1 Rating 380-440V	AC3 Rating 380-440V		Ordering Reference 4P	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
				H	W	D	A	Ø	B
45A	20A	11kW	ST CON 4/4	300	180	110	10 cage		115
70A	40A	22kW	ST CON 7/4	400	300	150	35 cage		150
100A	53A	30kW	ST CON 10/4	400	300	150	35 cage		150
125A	80A	45kW	ST CON 12/4	500	400	200	50 cage		200
160A	116A	55kW	ST CON 16/4	600	400	200	13	M6	240
200A	140A	75kW	ST CON 20/4	600	400	250	13	M6	240
275A	190A	90kW	ST CON 27/4	700	500	250	16	M8	250
400A	265A	132kW	ST CON 40/4	800	600	300	20	M10	290

Stop/Start units have a red twist to reset emergency stop and a green start pushbutton wired into a standard stop/start circuit. Additional terminals are provided for wiring in an E-stop loop.

- Auto or manual trip reset and test button



AC1 Rating 380-440V	AC3 Rating 380-440V		Ordering Reference 4P	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
				H	W	D	A	Ø	B
45A	20A	11kW	ST CON 4/4 STP	300	180	110	10 cage		115
70A	40A	22kW	ST CON 7/4 STP	400	300	150	35 cage		150
100A	53A	30kW	ST CON 10/4 STP	400	300	150	35 cage		150
125A	80A	45kW	ST CON 12/4 STP	500	400	200	50 cage		200
160A	116A	55kW	ST CON 16/4 STP	600	400	200	13	M6	240
200A	140A	75kW	ST CON 20/4 STP	600	400	250	13	M6	240
275A	190A	90kW	ST CON 27/4 STP	700	500	250	16	M8	250
400A	265A	132kW	ST CON 40/4 STP	800	600	300	20	M10	290