

Sheet Steel Enclosed Junction Boxes

- Insulator rating 1000V
- Bolt connection for cable lugs from 120mm² +
- IP2X terminal protection
- Padlockable hinged door enclosure
- Ingress protection IP55



Max cable size per phase	Nominal Rating I _e 415V	Ordering Reference 3P	Ordering Reference 4P	Ordering Reference 5P including bonded earth	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
					H	W	D	A	Ø	B

Units with individual screw down terminals (for bootlace ferrules)

35	125A	STJB 35/3	STJB 35/4	STJB 35/5	400	300	150	35 cage		200
70	192A	STJB 70/3	STJB 70/4	STJB 70/5	500	400	200	70 cage		210

Units with individually shrouded power terminals (for lugs)

120	250A	STJB 120/3	STJB 120/4	STJB 120/5	600	400	200	20	M10	230
185	350A	STJB 185/3	STJB 185/4	STJB 185/5	800	600	250	25	M12	320
300	500A	STJB 300/3	STJB 300/4	STJB 300/5	800	600	250	30	M16	320

Units with individual copper bars on insulators with all over shrouding (for lugs)

2 x 300	500A	STJB 500/3	STJB 500/4	STJB 500/5	1000	600	250	40	M12	390
2 x 400	630A	STJB 630/3	STJB 630/4	STJB 630/5	1000	600	300	50	M12	390
2 x 400	800A	STJB 800/3	STJB 800/4	STJB 800/5	1000	800	300	50	M12	390
2 x 400	1000A	STJB 1000/3	STJB 1000/4	STJB 1000/5	1200	800	300	60	M12	490

If you require any bespoke layouts or additions then please get in touch with our sales team.

All cables from one direction



Multiple cables per termination



Stainless Steel



Floor Standing Bespoke Units

