

Sheet Steel Enclosed UPS Bypass Switches I-II

Our range of single handle operation UPS Make-Before-Break bypass switches are designed to minimise the panel width and keep each set of cables separated. As standard they facilitate bypass cabling from one direction and the UPS from the other. However a variety of cable directions can be catered for.

- Make-Before-Break two position I-II
- Single handle operation
- BSEN 60947-3 conformity
- Fully load rated AC22A 415 - 690V
- Door interlocking padlockable handle
- Ingress protection IP55



Nominal Rating I _e 415V	Ordering Reference	Dimensions (mm) <small>*see inner front cover for reference diagram</small>					
		H	W	D	A	Ø	B
125A	ST BYUPS 12/4	600	400	300	20	M8	225
160A	ST BYUPS 16/4	600	400	300	20	M8	225
250A	ST BYUPS 25/4	800	600	400	25	M10	300
400A	ST BYUPS 40/4	800	600	400	30	M10	300
630A	ST BYUPS 63/4	1000	600	400	35	M10	400
800A	ST BYUPS 80/4	1200	600	400	40	M12	480
1000A	ST BYUPS 100/4	1200	800	400	40	M12	480
1250A	ST BYUPS 125/4	1400	800	400	40	M12	580



Key Interlocking

Units can be supplied with Castell or Fortress bolt interlocks to key exchange with your UPS internal bypass. Key switches to fit in the UPS can also be supplied if not fitted.



Auxiliary Contacts

Up to four can be fitted in each switching position. All auxiliary blocks are rated at AC11 4.5A 220-240V, 10A 24V

Colour	Order Reference	Legend	Action on closing	Action on opening
Red	EXNCAU2	N/C	early break	late make
Green	EXNCAU1V	N/O	late make	early break