



PURPLESEAL™ PS-C ALL-COMPOSITE FRAC PLUG

ZERO METALLIC CONTENT PLUS PREMIUM PERFORMANCE AT A GREAT PRICE

The PurpleSeal™ PS-C is an all-composite frac plug with ceramic buttons in the upper and lower slips, rated up to 10,000 psi.

Proprietary high-strength composite materials ensure uniform performance and durability. Interlocking castellations on the slips and end caps coupled with a planar interface between the slips and cones eliminate component rotation to ensure even, concentric slip expansion. With zero metallic content, PurpleSeal™ PS-C frac plugs consistently drill out in 6 minutes or less.

FEATURES & BENEFITS

- Lightweight materials that shred into small cuttings for industry leading drill-out performance
- Mix of compression molded and filament wound components for a debris profile that is fine, lightweight, and avoids large sized debris, even in challenging low-pressure wells
- Interlocking components to prevent spinning during drill-out
- Over one inch of seal engagement with casing when set
- Patented element backup mechanism that prevents casing erosion damage caused by seal extrusion failures
- Exceptional conformity to highly ovalized casing (10,000 psi test results available upon request)
- Pump down fin included with every plug (saves 25% more fluid each pump down versus competitors)
- Anti-preset features in the plug and wireline adapter kit
- No RIH speed restrictions when pumping



4.5 - 5.0"

5.5"

Matt Merron
Product Line Manager
972.623.7846

Ian Ansley
Houston Area
713.591.8464

Gilbert Rodríguez
Permian Region
432.853.6637

Adam Curry
Appalachia Region
724.882.9816

Todd Draeger
Rocky Mountains Region
970.380.8633

**FIND OUT MORE AT
[REPEATPRECISION.COM](https://www.repeatprecision.com)**

PURPLESEAL™ PS-C ALL-COMPOSITE FRAC PLUG

ZERO METALLIC CONTENT PLUS PREMIUM PERFORMANCE AT A GREAT PRICE

SPECIFICATIONS

Plug OD in.	Casing Size in.	Casing Weight lb/ft	Pressure rating psi	Plug ID in.	Plug OAL in.	Set Force lb	Casing Weight lb/ft	Max Vertical RIH Speed* without flowrate ft/min	Part Number
3.4	4.500	11.6-15.1	10,000	1.000	14.66	20,000	11.6-15.1	700	42671
	4.500	11.6-15.1	10,000				11.6-13.5	700	
3.6	5.000	23.2	9,000	1.000	14.66	20,000	15.1	500	24209
	5.000	23.2	9,000				23.2	700	
3.85	5.000	18.0-21.4	10,000	1.000	15.63	20,000	18.0	600	28403
							21.4	400	
4.25	5.500	20.0-26.8	10,000	1.000	17.00	25,000	20.0	700	
							23.0	500	42683
							26.8	350	
							17.0	650	
4.38	5.500	17.0	8,000	1.250	16.66	25,000	20.0	475	37512
		20.0-23.0	10,000				23.0	350	
4.8	6.000	23.0-26.0	8,000	1.500	17.13	30,000	23.0	400	35170
							26.0	300	

*Maximum recommended vertical running speed with no flowrate

Matt Merron
Product Line Manager
972.623.7846

Ian Ansley
Houston Area
713.591.8464

Gilbert Rodríguez
Permian Region
432.853.6637

Adam Curry
Appalachia Region
724.882.9816

Todd Draegert
Rocky Mountains Region
970.380.8633

**FIND OUT MORE AT
REPEATPRECISION.COM**