

# Adlib AAMP4

## Description

The Adlib AAMP4 is a compact, low-profile, 2-way bi-amp stage monitor system combining high output controlled and dispersion with contemporary design.

The AAMP4 features a high output, long excursion 15" (380mm) low frequency driver and a 1.4" (35mm) exit neodymium compression driver coupled to a 70° x 30° flat-fronted glass fibre horn. Constant SPL and consistent frequency is maintained at ear height when used as a single unit or as left and right pairs.

The AAMP4 is fitted with a black mild steel, round-hole front grill, which is backed with open-cell foam to protect the components from dust ingress.



Made in Liverpool England

## Specifications

System Type	2-Way Bass Reflex
LF Driver	15" Cone Transducer
HF Driver	1.4" Exit Neodymium Compression Driver
Frequency Range	55Hz – 18KHz ± 3dB
Nominal Impedance	LF 8 Ohms HF 8 Ohms
Power Handling	LF 600w AES 2400w peak HF 110w AES 440w peak
Sensitivity	98dB*
Dispersion	70° x 30°
Connectors	4 x Neutrik® NL4 speakON
Height	365mm
Width	690mm
Depth	533mm
Net Weight	34.5Kg

\*Sensitivity figures are measured in half-space conditions @ 2 metres with 1 watt input using band-limited pink noise, then referred to 1 metre.



## Materials & Fittings

Cabinet Construction	15mm BB Grade Birch Plywood
Finish	Black Polyurea Coating
Fittings	2 Mild Steel Bar Handles

## System Operation

Sub Bass	AA215DS Drum Sub
Accessories	Adlib Wedge Dolly & Flight Case Available
Cabling	LF +1 -1, HF +2 -2

Adlib Audio Ltd. reserve the right to alter any of the above specifications without further notice.