

Adlib AA121


Description

The AA121 is a compact, trapezoidal, 2-way passive full-range enclosure, featuring a 12" (300mm) low frequency transducer and a 1" (25mm) exit compression driver mounted on a 90° x 40° exponential horn flare. The high frequency compression driver utilises solid state Protection Circuitry (PTC) to protect the unit from possible overload (amplifier clipping) situations.

The AA121 is fitted with a black mild steel, round-hole front grill, which is backed with open-cell foam to protect the components from dust ingress.

Applications

The AA121 is ideally suited to full-range applications calling for an efficient passive enclosure such as live club performance, places of worship and AV presentations.



Made in Liverpool England



Specifications

System Type	2-Way Bass Reflex
LF Driver	12" Cone Transducer
HF Driver	1" Exit Compression Driver
Frequency Range	70Hz - 18KHz ± 3dB
Nominal Impedance	8 Ohms
Power Handling	450w AES
Sensitivity	97dB*
Dispersion	90° x 40°
Connectors	2 x Neutrik® NL4 speakON
Pin Connectors	Full Range 1+ / 1-
	Link Through 2+ / 2-

Height	535mm
Width	375mm
Depth	310mm
Net Weight	20Kg

Materials & Fittings

Cabinet Construction	15mm BB Grade Birch Plywood
Finish	Textured Black Paint

*Sensitivity figures are measured in half-space conditions @ 2 metres with 1 watt input using band-limited pink noise, then referred to 1 metre.

Adlib Audio Ltd. reserve the right to alter any of the above specifications without further notice.