



24' Wrangler
(shown with optional equipment)

WRANGLER LIVESTOCK TRAILER

BUILT ON A HERITAGE OF INNOVATION

A heritage of EBY quality and styling

Featuring EBY's hallmark quality and styling, Wrangler offers unmatched versatility with a broader selection of widths, heights and custom options. Engineered to perform and built to last, Wrangler will remain a trusted companion for years to come.

Standard Sizes:

Lengths: 20', 22' and 24'

Widths: 7'6" and 8'

Height: 6'6"

Custom sizes available

800-292-4752 • www.mheby.com

Wrangler Livestock Trailer

Standard Features



Multi-function fender lights



Cast aluminum front and rear corners



Low-step rear door



Fully framed and full-height side door



Heavy-duty 12" extruded aluminum bottom rail



Dexter torsion ride axles

Popular Options



Rolling partition gate



Curb-side ramp



Plexiglas closures

Additional options and custom sizes available. Refer to EBY's [Livestock Trailer Brochure](#) for optional Combo, Trophy, Trophy Plus, and Final Drive convenience packages.




800-292-4752
www.mheby.com




EBY is a proud member of The National Association of Trailer Manufacturers, dedicated to improving trailer safety and performance. EBY trailers are manufactured in compliance with NATM guidelines.

STANDARD SPECIFICATIONS	
Floor Lengths	20', 22' and 24' (custom sizes available)
Outside Width	7'6" and 8' (custom sizes available)
Inside Height	6'6"
GVWR	15,000 lbs
Axles	(2) 7,000# Rubber ride (grease packed bearings); 102" wide (additional options available)
Wheels	16" x 6" Heavy-duty steel, 8-lug (additional options available)
Tires	(4) ST235/85R16 steel belted radials, load range E (additional options available)
Brakes	12" x 2" Electric on both axles (additional options available)
Safety Equipment	Two chains and electronic break-away kit
Nose	.080 aluminum smooth sheet sides and front
Coupler	2 ⁵ / ₁₆ " Ball coupler (20,000# ball rating) with steel hitch post section and aluminum front gusset, adjustable height
Side Wall	Extruded aluminum slats welded to 1" x 3" aluminum tubes, spaced no more than 18" on center. Choice of slat patterns. 6" openings are notched for optional closures.
Floor	.115 6061 T-6 aluminum diamond plate with (4) 1" high ridges, ridged longitudinally on 19" centers
Side Door	33" Wide, curb side escape door
Rear Door	Full-swing with (3) 4" extruded aluminum offset hinges for extended swing radius; 35" sliding door on roadside
Roof Sheet	One-piece .040 aluminum
Partition	Divider at front of wheel wells, with outside release slam latch
Lights	LED inside and out; 12-volt D.O.T. approved


Slat Patterns




Slat Pattern A



Slat Pattern B



Slat Pattern C



Slat Pattern D

AUTHORIZED DEALER



All EBY trailers feature Dexter axles.

Rev. 3/18