



30' Ruff Neck Punch-Side
(shown with optional equipment)

PUNCH-SIDE RUFF NECK LIVESTOCK TRAILER

BUILT ON A HERITAGE OF INNOVATION

EBY's legendary top-of-the-line design

Ruff Neck—our most rugged design—equips commercial livestock haulers, show enthusiasts, commercial swine operators and draft horse transporters with exceptional hauling capability. Engineered for unmatched durability, and offering an impressive level of customization, Ruff Neck sets the industry standard for delivering extraordinary dependability year after year.

Available Sizes:

Lengths: 24'6" to 35'
Widths: 7'3", 8' and 8'6"
Heights: 6'6", 7' and 7'6"

Custom sizes available

800-292-4752 • www.mheby.com

Ruff Neck Punch-Side Gooseneck Livestock Trailer

Standard Features



Multi-function fender lights



Cast aluminum front and rear corners




Low-step rear door



Fully framed and full-height side door



High-button aluminum diamond plate floor



All-aluminum subframe

Popular Options



Rolling partition gate



Spare tire and wheel




Available in a variety of colors


Additional options and custom sizes available. Refer to EBY's [Livestock Trailer Brochure](#) for optional Trophy, Trophy Plus, and Final Drive convenience packages.

| STANDARD SPECIFICATIONS | |
|-------------------------|--|
| Floor Lengths | 24'6" to 35' (custom sizes available) |
| Outside Width | 7'3", 8' and 8'6" |
| Inside Height | 6'6", 7' and 7'6" (custom sizes available) |
| GVWR | 19,000 lbs – 8K axles; 25,000 lbs – (3) 8K axles; 25,000 lbs – 10K axles |
| Axles | Rubber ride (grease packed bearings); 102" wide - (2) 8,000# on 24'6" and 26' lengths - (2) 10,000# on 27'6" and longer lengths |
| Wheels | 17.5" x 6.75" Heavy-duty steel, 8-lug |
| Tires | (4) 235/75R17.5 steel belted radials, load range H |
| Brakes | 12 1/4" x 3 3/8" Electric on both axles; 12 1/4" x 4" on 10K axles |
| Safety Equipment | Two chains and electronic break-away kit |
| Nose | .080 aluminum smooth sheet sides and front |
| Coupler | 2 5/16" Ball coupler (30,000# ball rating) with steel hitch post section and aluminum front gusset, adjustable height |
| Side Wall | .075 thick aluminum sheet riveted to extruded aluminum hat-shaped side posts on 18" centers. Posts can be notched to accept optional closure panels. |
| Punch Patterns | Standard punch patterns A, B, C and D (custom punch patterns available on special request) |
| Floor | .115 6061 T-6 aluminum diamond plate with (4) 1" high ridges, ridged longitudinally on 19" centers |
| Side Door | 28 1/2" Wide, curb side escape door |
| Rear Door | Full-swing with (3) 4" extruded aluminum offset hinges for extended swing radius; sliding door on roadside |
| Roof Sheet | One-piece .040 aluminum |
| Partition | Divider at front of wheel wells, with outside release slam latch |
| Lights | LED inside and out; 12-volt D.O.T. approved |


Punch Patterns




Punch Pattern A



Punch Pattern B



Punch Pattern C



Punch Pattern D



800-292-4752
www.mheby.com



EBY is a proud member of The National Association of Trailer Manufacturers, dedicated to improving trailer safety and performance. EBY trailers are manufactured in compliance with NATM guidelines.

