



23K Low-Profile
(shown with optional equipment)

23K GVW BUMPER-PULL LOW-PROFILE EQUIPMENT TRAILER

GREATER PAYLOAD THAN A STEEL TRAILER

A heavier-duty low-profile design

The 23K Low-Profile design takes EBY's legendary engineering to the extreme. Boasting the same fuel-efficient, low-maintenance aluminum as all of our trailers, and equipped with an industrial-strength frame, heavy-duty wheels, and rock-solid dual drop-legs, the 23K Low-Profile is a dependable work horse. With an impressive array of options—lockable toolbox, spare tire, winch and much more—this trailer will be with you on the job for years to come.

The Benefits of Aluminum Far Outweigh Steel:

- Lower trailer weight
- Higher payload capacity
- Improved fuel economy
- Reduced maintenance costs

800-292-4752 • www.mheby.com

23K GVW Bumper-Pull Low-Profile Equipment Trailer

Features



3'3" Beavertail with 60" ramps for easy loading and unloading. Wood inlay ramps are optional.



12K Dual Bulldog 2-speed drop-legs provide added stability



Heavy-duty steel wheels with two 10K Dexter torsion ride axles to handle whatever you need to haul

Available Options



Outfit your trailer with a lockable A-frame toolbox or spare tire in front of the bulkhead

STANDARD SPECIFICATIONS

GVWR	23,000 lbs
Tare Weight	4,880 lbs
Length	22'6" Deck, plus 3'3" beavertail and 5' long A-frame (31' total overall)
Width	102" (overall)
Coupler	Adjustable 25K lunette ring
Landing Gear	12K 2-Speed dual Bulldog drop-legs
Axles	(2) 10K Dexter torsion ride on 42" spacing
Brakes	Electric brakes with break-a-way kit
Wheels	(4) 17.5" x 6.75" Heavy-duty steel wheels; 8-lugs
Tires	(4) 235/75R17.5, Load range H, 125psi
Floor	1 1/2" Extruded aluminum planks running front to back; wood nailers on outside of flat deck, supported by 4" Z-shaped HD cross members 16" O.C.; extruded outside rails with integrated tie-down slots
Frame	15.875" Two-piece frame rails
Tie Downs	(4) Heavy-duty extruded aluminum; adjustable
Fenders	82" Between fenders; mudflaps on rear
Beavertail	39" integrated wood running front-to-back at 14-degree angle
Ramps	60"L x 24"W with spring-assist fold-up; constructed of 5" aluminum channel and wood inlays
Wiring Plug	7-pin RV plug
Lights & Wiring	12 Volt DOT approved LED with ATA color coded, sealed wiring harness; meets all U.S. and Canadian regulations



800-292-4752
www.mheby.com



EBY is a proud member of The National Association of Trailer Manufacturers, dedicated to improving trailer safety and performance. EBY trailers are manufactured in compliance with NATM guidelines.

AUTHORIZED DEALER

